

Last modification

2022-11-12

ASTRID OY33-BK3C 9329501054734



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white.

Overview

Family nameAstridCategoriesOystersMountingSurfaceThis item includesDiffuser

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorSatin,Clear,BlackFixture MaterialMetal,Polycarbonate

Canopy ColorWhiteShade ColorFrostShade MaterialPlasticDiffuser ColorOpal

Diffuser Material Polycarbonate

Size

Fixture Diameter (cm) 33.0

Fixture Height (cm) 6.5

Fixture Projection (cm) 6.5

Canopy Diameter (cm) 25.5

Canopy Projection (cm) 1.5

Diffuser Diameter (cm) 33.0

Diffuser Height (cm) 6.0

Specification

1

Voltage Input 240V Wattage (max) 18



Globe Type LED integrated SMD

Globe / Light Source qty 1
Globe / Light Source included Yes
Lumens 1400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableNoPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth


Replacement Warranty *3 Years

<u>Barcode</u>

GTIN 9329501054734

Image -dimensions











Last modification

2022-11-12

ASTRID OY33-OK3C 9329501054758



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white.

Overview

Family nameAstridCategoriesOystersMountingSurfaceThis item includesDiffuser

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorSatin,Clear,OakFixture MaterialMetal,Polycarbonate

Canopy ColorWhiteShade ColorFrostShade MaterialPlasticDiffuser ColorOpal

Diffuser Material Polycarbonate

<u>Size</u>

Fixture Diameter (cm) 33.0

Fixture Height (cm) 6.5

Fixture Projection (cm) 6.5

Canopy Diameter (cm) 25.5

Canopy Projection (cm) 1.5

Diffuser Diameter (cm) 33.0

Diffuser Height (cm) 6.0

Specification

1

Voltage Input 240V Wattage (max) 18



Globe Type LED integrated SMD

Globe / Light Source qty 1
Globe / Light Source included Yes
Lumens 1400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableNoPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth


Replacement Warranty *3 Years

<u>Barcode</u>

GTIN 9329501054758

Image -dimensions











Last modification

2022-11-12

ASTRID OY33-SL3C 9329501054727



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white.

Overview

Family nameAstridCategoriesOystersMountingSurfaceThis item includesDiffuser

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorSatin,Clear,SilverFixture MaterialMetal,Polycarbonate

Canopy ColorWhiteShade ColorFrostShade MaterialPlasticDiffuser ColorOpal

Diffuser Material Polycarbonate

Size

Fixture Diameter (cm) 33.0

Fixture Height (cm) 6.5

Fixture Projection (cm) 6.5

Canopy Diameter (cm) 25.5

Canopy Projection (cm) 1.5

Diffuser Diameter (cm) 33.0

Diffuser Height (cm) 6.0

Specification

1

Voltage Input 240V Wattage (max) 18



Globe Type LED integrated SMD

Globe / Light Source qty 1
Globe / Light Source included Yes
Lumens 1400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableNoPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth


Replacement Warranty *3 Years

<u>Barcode</u>

GTIN 9329501054727

Image -dimensions











Last modification

2022-11-12

ASTRID OY33-CH3C 9329501054741



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white.

Overview

Family name Astrid Categories Oysters Mounting Surface This item includes Diffuser

Usage Indoor Lighting, Trade Selection

Color / Material

Fixture Color Satin, Silver, Chrome **Fixture Material** Metal, Polycarbonate

Canopy Color White **Shade Color** Frost **Shade Material** Plastic Diffuser Color Opal

Diffuser Material Polycarbonate

Size

Fixture Diameter (cm) 33.0 Fixture Height (cm) 6.5 6.5 Fixture Projection (cm) Canopy Diameter (cm) 25.5 Canopy Projection (cm) 1.5 Diffuser Diameter (cm) 33.0 Diffuser Height (cm) 6.0

Specification

1

240V **Voltage Input** Wattage (max) 18



Globe Type LED integrated SMD

Globe / Light Source qty 1
Globe / Light Source included Yes
Lumens 1400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableNoPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)

Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth

Replacement Warranty *3 Years

<u>Barcode</u>

GTIN 9329501054741

Image -dimensions

