2022-11-12



Last modification

ASTRID 0Y43-BK3C 9329501054772



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white. The fixture is also triac dimmable.

Overview

Family nameAstridCategoriesOystersMountingSurfaceThis item includesDiffuser

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorSatin,Clear,BlackFixture MaterialMetal,Polycarbonate

Canopy ColorWhiteShade ColorFrostShade MaterialPlasticDiffuser ColorOpal

Diffuser Material Polycarbonate

<u>Size</u>

Fixture Diameter (cm) 43.0

Fixture Projection (cm) 8.5

Canopy Diameter (cm) 36.0

Canopy Projection (cm) 1.5

Diffuser Diameter (cm) 43.0

Specification

Voltage Input 240V Wattage (max) 30

Globe Type LED integrated SMD

Globe / Light Source qty



Globe / Light Source included Yes Lumens 2400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableYesPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth


Replacement Warranty *3 Years

Barcode

GTIN 9329501054772

Image -dimensions











Last modification

2022-11-12

ASTRID OY43-OK3C 9329501054796



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white. The fixture is also triac dimmable.

Overview

Family nameAstridCategoriesOystersMountingSurfaceThis item includesDiffuser

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorSatin,Clear,OakFixture MaterialMetal,Polycarbonate

Canopy ColorWhiteShade ColorFrostShade MaterialPlasticDiffuser ColorOpal

Diffuser Material Polycarbonate

<u>Size</u>

Fixture Diameter (cm) 43.0

Fixture Projection (cm) 8.5

Canopy Diameter (cm) 36.0

Canopy Projection (cm) 1.5

Diffuser Diameter (cm) 43.0

Specification

Voltage Input 240V Wattage (max) 30

Globe Type LED integrated SMD

Globe / Light Source qty



Globe / Light Source included Yes Lumens 2400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableYesPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth


Replacement Warranty *3 Years

Barcode

GTIN 9329501054796

Image -dimensions











Last modification

2022-11-12

ASTRID 0Y43-SL3C 9329501054765



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white. The fixture is also triac dimmable.

Overview

Family nameAstridCategoriesOystersMountingSurfaceThis item includesDiffuser

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorSatin,Clear,SilverFixture MaterialMetal,Polycarbonate

Canopy ColorWhiteShade ColorFrostShade MaterialPlasticDiffuser ColorOpal

Diffuser Material Polycarbonate

Size

Fixture Diameter (cm) 43.0

Fixture Projection (cm) 8.5

Canopy Diameter (cm) 36.0

Canopy Projection (cm) 1.5

Diffuser Diameter (cm) 43.0

Specification

Voltage Input 240V Wattage (max) 30

Globe Type LED integrated SMD

Globe / Light Source qty



Globe / Light Source included Yes
Lumens 2400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableYesPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth


Replacement Warranty *3 Years

Barcode

GTIN 9329501054765

Image -dimensions











Last modification

2022-11-12

ASTRID 0Y43-CH3C 9329501054789



The ASTRID ceiling light can easily complement any home due to its clean edge design, and contrast trim. The special opaline diffuser provides a very even light. Output color temperature can be controlled internally by a slide switch to select warm, natural or cool white. The fixture is also triac dimmable.

Overview

Family nameAstridCategoriesOystersMountingSurfaceThis item includesDiffuser

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorSatin, Silver, ChromeFixture MaterialMetal, Polycarbonate

Canopy ColorWhiteShade ColorFrostShade MaterialPlasticDiffuser ColorOpal

Diffuser Material Polycarbonate

Size

Fixture Diameter (cm) 43.0

Fixture Projection (cm) 8.5

Canopy Diameter (cm) 36.0

Canopy Projection (cm) 1.5

Diffuser Diameter (cm) 43.0

Specification

Voltage Input 240V Wattage (max) 30

Globe Type LED integrated SMD

Globe / Light Source qty



Globe / Light Source included Yes Lumens 2400

Color Temperature Warm White; Natural White; Cool White

Color Kelvin 3 CCT (3000k - 4000k - 6500k)

Color Rendering>80DimmableYesPower Factor>0.90Surge ProtectionYes (1.5 Kva)

Beam Angle (degree) 180

Electrical Protection CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP20
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)

Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth

Replacement Warranty *3 Years

Barcode

GTIN 9329501054789

Image -dimensions

