

AT4105/PIR

AT4105/PIR/WHT

Surface mount PIR sensor - 6m



ORDERING INFORMATION

Order code	13947
Description	PIR sensor 6m- surface mount - White
Item Code	AT4105/PIR/WHT

MECHANICAL

Body Material	Polycarbonate
Fitting Colour	White
Installation Type	Surface mount
IP Rating	IP20

ELECTRICAL

Electrical Rating	Class II
Input Frequency	50 Hz
Input voltage	230V~
Working Temp Range	-20 to 40 °C

SENSOR (S SUFFIX)

Adjustable Detection Area / Sensitivity	No
Adjustable Hold Time	Yes
Adjustable Standby Level	No
Adjustable Standby Period	No
Corridor Function	No
Dawn Reset	No
Detection Range	6 m
Dusk Mode	Yes
Lux Adjustment	Yes

Lux Range	<3 to 2000 lx
Manual Override	No
Sensor Type	PIR
Switched Output	Yes
Switched Output Rating	2000 W
Time Delay	10s to 15m


COMPLIANCE

Standards	AS/NZS 60669.1 AS/NZS 60669.2.1 EN/IEC 55015 IEC 61000.3 IEC 61000.4
-----------	--

DIMENSIONS

Product Diameter	115 mm
Product Height	22 mm

LINE DRAWINGS



AT4105/MW

AT4105/MW/WHT

Surface mount microwave sensor - 12m



ORDERING INFORMATION

Order code	13776
Description	Microwave sensor 12m-surface mount - White
Item Code	AT4105/MW/WHT

MECHANICAL

Body Material	Polycarbonate
Fitting Colour	White
Installation Type	Surface mount
IP Rating	IP20

ELECTRICAL

Electrical Rating	Class II
Input Frequency	50 Hz
Input voltage	230V~
Working Temp Range	-20 to 40 °C

SENSOR (S SUFFIX)

Adjustable Detection Area / Sensitivity	Yes
Adjustable Hold Time	Yes
Adjustable Standby Level	No
Adjustable Standby Period	No
Corridor Function	No
Dawn Reset	No
Detection Range	12 m
Detection Angle	360
Dusk Mode	Yes

Lux Adjustment	Yes
Lux Range	<3 to 2000 lx
Manual Override	No
Sensor Type	Microwave
Switched Output	Yes
Switched Output Rating	2000 W
Time Delay	10s to 12m

COMPLIANCE

Standards	AS/NZS 60669.1 AS/NZS 60669.2.1 EN/IEC 55015 IEC 61000.3 IEC 61000.4 AS/NZS 4268
-----------	---

DIMENSIONS

Product Diameter	115 mm
Product Height	22 mm

LINE DRAWINGS

