AZURE CEILING FAN





Installation Locations:

Indoor only

Motor:

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 32°

Wall Controller Speed Capacitor Values:

 $3.5\mu F \& 2\mu F$

Recommended Height:

There should be at least 2.1m between the lowest point

of the fan blades and the floor.

Top of canopy cover to lowest point of the fan Rotational Diameter:

1220mm (48") Blade Sweep

without light fittings attached:

Approximately 350mm

Weight Including Packaging:

Complete fan 1220mm (48") - 6.6kg

16 Pole, 153mm x 15mm motor

Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet Packaging Dimensions (cm): operation and long life.

55.1L x 25.4W x 26.4H

Motor Housing:

Materials: Pressed Steel

White, Brushed Chrome

Accessories (Supplied separately): Remote Control

Extension Down Rod 21mm diameter (wire harness

included)

T-Hook for ceiling roses

Blades:

1220mm (48") Straight Style

Materials: NZ plywood, Painted finish

Available Motor Housing Colours:

Blade Pitch: 12°

Warranty

1 year standard warranty "in home" on electronic parts 2 years standard warranty "in home" on mechanical

parts (including motors)

3 years extended warranty on motor only (excluding

labour)

Available Blade Colours: White. Brushed Silver

Extra Information:

Introduced into the HPI range in 2016

3 Speed wall controller

Reversible

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA

Energy Star compliance.

Azure fan 1220mm (48")	HIGH	MED	LOW
RPMS	182	145	102
WATTS	52.4	36.3	20.9
AIRFLOW: CFM* / CMH*	6354/10843	5061/8637	3785/6459
EFFICIENCY^: (CFM / Watt) / (CMH / Watt)	121/207	139/238	181/309

^{*} CFM = Cubic Feet per Minute / CMH = Cubic Meters per Hour

[^] Efficiency measured as airflow rate per Watt.

[#] For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au