

Last modification

2022-11-29

G A609B22OP860 9329501059456





Overview

Family name B22
Categories Globes

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorWhite,OpalFixture MaterialPolycarbonateShade MaterialPolycarbonate

Diffuser Color Opal

Diffuser Material Polycarbonate

<u>Size</u>

Fixture Diameter (cm) 6.0 Fixture Height (cm) 11.2

Specification

240V **Voltage Input** Wattage (max) 9 **Globe Type** B22 900 Lumens **Color Temperature** Daylight 6000k **Color Kelvin Color Rendering** >80 **Dimmable** No >0.85 **Power Factor** Yes (0.5 Kva) **Surge Protection** Beam Angle (degree) 360

IP rating IP20 Approvals RCM

Care Instructions Wipe clean with a dry cloth

Replacement Warranty *3 Years

All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.

NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.




<u>Barcode</u>

GTIN

9329501059456

Image -dimensions





All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000. NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.



Last modification

2022-11-29

G A609B22OP840 9329501057544





Overview

Family name B22/A60 Categories Globes

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorWhite,OpalFixture MaterialPolycarbonateShade MaterialPolycarbonate

Diffuser Color Opal

Diffuser Material Polycarbonate

<u>Size</u>

Fixture Diameter (cm) 6.0 Fixture Height (cm) 11.2

Specification

 Voltage Input
 240V

 Wattage (max)
 9

 Globe Type
 B22

 Lumens
 870

Color Temperature Natural White

Color Kelvin4000kColor Rendering>80DimmableNoPower Factor>0.85Surge ProtectionYes (0.5 Kva)Beam Angle (degree)360

IP rating IP20 Approvals RCM

Care Instructions Wipe clean with a dry cloth

Replacement Warranty *3 Years




<u>Barcode</u>

GTIN

9329501057544

Image -dimensions





All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000. NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.



Last modification

2022-11-29

G A609B22OP830 9329501058718





Overview

Family name B22/A60 Categories Globes

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture ColorWhite,OpalFixture MaterialPolycarbonateShade MaterialPolycarbonate

Diffuser Color Opal

Diffuser Material Polycarbonate

Size

Fixture Diameter (cm) 6.0 Fixture Height (cm) 11.2

Specification

 Voltage Input
 240V

 Wattage (max)
 9

 Globe Type
 B22

 Lumens
 850

Color TemperatureWarm WhiteColor Kelvin3000kColor Rendering>80DimmableNoPower Factor>0.85Surge ProtectionYes (0.5 Kva)Beam Angle (degree)360

IP rating IP20
Approvals RCM

Care Instructions Wipe clean with a dry cloth

Replacement Warranty *3 Years

All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.

NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.




<u>Barcode</u>

GTIN

9329501058718

Image -dimensions





All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000. NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.