

COMET SERIES

LED Tri-CCT **DIMMABLE** Centre Tilt Recessed downlights

3000K | 4200K | 6000K

3 CCT IN ONE FITTING



General Lighting



COMET01



COMET03



COMET02



COMET04

Product Features:

- Input voltage range: 185-265V AC 50/60Hz
- Constant current LED driver included
- Material: aluminium body & PMMA lens
- Heatsink: aluminium
- LED chips: 1pc COB LED
- Power factor: ≥0.9
- Ambient temp: -20 to 40°C
- Flex & plug: COMET01&03: 1640mm; COMET02&04: 1460mm
- Suitable for 2-way switching
- Suitable for dimming
- Suitable for 3 wire motion & microwave sensors

30,000hr
Lifetime

50°
Beam Angle


IP20
Rated

3YEAR
Replacement
Warranty

IC-F
ABUTTED &
COVERED




TRI-CCT
SWITCH
ON THE
FITTING




Tested & Recommended Dimmers:

Brand	Part No.	PCS per Dimmer
CLA	LYNX & VELA	1-8pcs
Diginet	MEDM & MMDM/RT	
CLIPSAL	32ELEDM-WE, 32E450TM, 32E450LM, 32E450UDM & 31E2PUDM	
HPM	CAT250L, CAT250T & CAT400T	



COMET01 & 03



COMET02 & 04

Part No.	Description	Kelvin	Lumens	Watt	CRI	Diam	Depth	Cut Out	Carton QTY
COMET01	D/L LED DIMM C/TILT MATT BL RND LOW GLARE Tri	3000/4200/6000K	750/850/800lm	10W	80	Ø100mm	107mm	Ø90mm	1/24
COMET02	D/L LED DIMM C/TILT MATT Brushed Nickel Tri	3000/ 4200/ 6000K	800/900/ 850lm	10W	80	Ø100mm	85mm	Ø70-90mm	1/24
COMET03	D/L LED DIMM C/TILT MATT WH RND LOW GLARE Tri	3000/ 4200/ 6000K	750/850/ 800lm	10W	80	Ø100mm	107mm	Ø90mm	1/24
COMET04	D/L LED DIMM C/TILT MATT WH RND Tri	3000/ 4200/ 6000K	800/900/ 850lm	10W	80	Ø100mm	85mm	Ø70-90mm	1/24