

Last modification 2022-12-06

KATO DL110-NK3C
9329501049778



The KATO is a round dimmable LED recessed downlight with the added convenience of color changing technology. Constructed of PC, Aluminium and PMMA and an IC4 rating for excellent heat dissipation technology for the LED array the KATO is suitable for almost any environment.

Overview

Family name	Kato
Categories	Downlights
Mounting	Recess
Usage	Indoor Lighting,Trade Selection

Color / Material

Fixture Color	Frost,Nickel
Fixture Material	Aluminium,Nylon
Diffuser Color	Frost
Diffuser Material	Polycarbonate

Size

Fixture Diameter (cm)	11.3
Fixture Height (cm)	6.0
Cut Out	9

Specification

Voltage Input	240V
Wattage (max)	10
Globe Type	LED integrated SMD
Globe / Light Source qty	1
Globe / Light Source included	Yes
Lumens	850
Color Temperature	Warm White; Natural White; Cool White
Color Kelvin	3 CCT (3000k - 4000k - 5700k)
Color Rendering	>84
Dimmable	Yes

All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

Power Factor	>0.85
Surge Protection	Yes
Beam Angle (degree)	120
Control Gear Included	Yes-integrated
Insulation class	IC-4
IP rating	IP44
Approvals	RCM
Assembly Required	No
Box Contents	Instruction
Installation Required	Yes (by Licensed Electrician only)
Care Instructions	Do not use strong liquid cleaners,Wipe clean with a dry cloth
Replacement Warranty	*3 Years

Barcode

GTIN 9329501049778

Image -dimensions





