

Highbay Accessories

Microwave dim sensor



FEATURES

- · Microwave motion detecting
- 3 or 2 step dimming function
- · Daylight threshold
- 15m maximum installation height suitable for most warehouses
- Setting adjustable remotely through remote controller (213979)
- Plug and play sensor for easy installation

Include

Microwave dimming Sensor

Order Code	Part No.	Model No.	Accessories
333409	333409	ECMMSC-H	Microwave Sensor To Suit Energetic Ark and Ark Pro LED Highbay
213979	213979	HD03R	Sensor Remote Controller With Memory for Ark and Ark Pro Highbay, V Battens and Tempest G3 WPF Batten

Microwave Sensor Spec

Stand-by Power	<0.5W	
Operating Frequency	5.8GHz±75MHz	
Transmitting power	<0.3mW	
Hold time	5s/30s/1min/3min/5min/10min/20min/30min	
Stand-by DIM Level	10%/20%/30%/50%	
Stand-by Period	0s/10s/30s/1min/5min/10min/30min/+∞	
Detection Area	25%/50%/75%/100%	
Daylight Sensor	2Lux/10Lux/30Lux/50Lux/80Lux/120Lux/Disable	
Detecting Radius	Max,ø14m/45.92ft (ceiling mounted)	
Mounting Height	15m/49.2ft (ceiling mounted)	
Operating Temperature	-20°C~+60°C	
Storage Temperature	Temperature: -40 °C +80 °C ; Humidity: 10%-95% (non-condensing)	
IP Rating	IP65	
Dimension	φ50*36mm	
Net Weight	76g	



Microwave dim sensor

Detection coverage

Typical installation height 15m

This figure indicates the maximum distance at the highest mounting height with 100% sensitivity.

