

Features



- Multi-Watt
- High lumen efficacy @200Lm/W
- Integrated dimmable driver
- Die-cast aluminium construction

Applications


Commercial, Industrial, Facilities,
Warehouses, Centres, Airport Hangers

Warranty

5 years



333454, 333455



333474, 333475, 333485

Product Data

Order Code	Part No.	Wattage	CCT	Lumen Output	Weight (kg)
333454	333454	200 / 180 / 150 / 120W	4000K	40,000 - 24,000Lm*	3.57
333455	333455	200 / 180 / 150 / 120W	5000K	40,000 - 24,000Lm*	3.57
333474	333474	150 / 120 / 100 / 70W	4000K	30,000 - 14,000Lm**	3.0
333475	333475	150 / 120 / 100 / 70W	5000K	30,000 - 14,000Lm**	3.0
333485	333485	100 / 90 / 70 / 50W	5000K	20,000 - 10,000Lm***	3.0

[1] Operating temperature: -20°C~+50°C

[2] Voltage: 220-240V

[3] PF: 0.9

[4] *40,000 / 36,000 / 30,000 / 24,000Lm

[5] **30,000 / 24,000 / 20,000 / 14,000Lm

[6] ***20,000 / 18,000 / 14,000 / 10,000Lm

Optional Accessories

Item	Order Code
Microwave Sensor	333499
Remote Control	213979
Pole Mount Bracket for 200W	333609
Pole Mount Bracket for 100W/150W	333619
Surface Mount Bracket for 100W/150W/200W	333589



Specifications are for reference only and may be changed without prior notice.