

SUMMARY

The Destiny Plus is a highly efficient edge-lit panel. Engineered using a PMMA light guide to deliver a lighter, brighter and stronger result. It's also incredibly slim at only 15mm thin. It double insulated and features a pre-wired flex and plug for quick and easy installation. It has a CRI rating of Ra>80 and a MacAdams rating of SDCM<4. Built to last, it features an aluminium frame that is finished in smooth powder-coating for durability and an opal polycarbonate diffuser.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	223324
Voltage	220-240V
Wattage	50W
Lumen Output	5000Lm
CCT	4000K
IP Rating	IP40
UGR Rating	UGR<22
MacAdams Rating	SDCM≤4
CRI Rating	Ra≥80
Beam Angle	110°
Light Source	SMD Chips
Driver	Remote Flicker-Free
Dimmable	No
Connection	1.2 flex and plug
Construction	Extruded aluminium frame / Opal polycarbonate diffuser
Finish	Powder coated
Fitting Colour	White
PF	0.9
Net Weight (kg)	4.31
Lifetime L70B50	50,000 hours
Warranty	5 years



SUMMARY

The Destiny Plus is a highly efficient edge-lit panel. Engineered using a PMMA light guide to deliver a lighter, brighter and stronger result. It's also incredibly slim at only 15mm thin. It double insulated and features a pre-wired flex and plug for quick and easy installation. It has a CRI rating of Ra>80 and a MacAdams rating of SDCM<4. Built to last, it features an aluminium frame that is finished in smooth powder-coating for durability and an opal polycarbonate diffuser.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	223314
Voltage	220-240V
Wattage	32W
Lumen Output	3400Lm
CCT	4000K
IP Rating	IP40
UGR Rating	UGR<22
MacAdams Rating	SDCM≤4
CRI Rating	Ra≥80
Beam Angle	110°
Light Source	SMD Chips
Driver	Remote
Dimmable	No
Connection	1.2 flex and plug
Construction	Extruded aluminium frame / Opal polycarbonate diffuser
Finish	Powder coated
Fitting Colour	White
PF	0.9
Net Weight (kg)	2.05
Lifetime L70B50	50,000 hours
Warranty	5 years



SUMMARY

The Destiny Plus is a highly efficient edge-lit panel. Engineered using a PMMA light guide to deliver a lighter, brighter and stronger result. It's also incredibly slim at only 15mm thin. It double insulated and features a pre-wired flex and plug for quick and easy installation. It has a CRI rating of Ra>80 and a MacAdams rating of SDCM<4. Built to last, it features an aluminium frame that is finished in smooth powder-coating for durability and an opal polycarbonate diffuser.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	223304
Voltage	220-240V
Wattage	32W
Lumen Output	3400Lm
CCT	4000K
IP Rating	IP40
UGR Rating	UGR<22
MacAdams Rating	SDCM≤4
CRI Rating	Ra≥80
Beam Angle	110°
Light Source	SMD Chips
Driver	Remote
Dimmable	No
Connection	1.2 flex and plug
Construction	Extruded aluminium frame / Opal polycarbonate diffuser
Finish	Powder coated
Fitting Colour	White
PF	0.9
Net Weight (kg)	1.95
Lifetime L70B50	50,000 hours
Warranty	5 years

