

### SUMMARY

The Emilite is an adjustable modular downlight ideal for commercial and residential applications. Engineered to deliver high lumen efficacy, this downlight features a remote dimmable driver, allowing it to be safely installed under ceiling insulation. The Emilite is required to be installed in conjunction with the Emilite downlight holder. It's also a retrofit solution to traditional GU10 and MR16 style downlights where the existing holder may be used.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

### PRODUCT DATA

Order Code	262003
Voltage	220-240V
Wattage	10.5W
Lumen Output	800Lm
CCT	5000K
IP Rating	IP20
Beam Angle	60°
Light Source	SMD Chips
Driver	Remote
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)
Connection	1.2 flex & plug
Construction	Aluminium body / faceted reflector
Fitting Colour	Black
PF	0.9
Net Weight (kg)	0.24
Lifetime L70B50	35,000 hours
Warranty	5 years

### OPTIONAL ACCESSORIES

ITEM	ORDER CODE	ITEM	ORDER CODE
Fixed Holder (White)	292001	Gimbal Holder (Satin Chrome)	292004
Gimbal Holder (White)	292003		



## SUMMARY

The Emilite is an adjustable modular downlight ideal for commercial and residential applications. Engineered to deliver high lumen efficacy, this downlight features a remote dimmable driver, allowing it to be safely installed under ceiling insulation. The Emilite is required to be installed in conjunction with the Emilite downlight holder. It's also a retrofit solution to traditional GU10 and MR16 style downlights where the existing holder may be used.



			<ul style="list-style-type: none"> <li> <b>VEET</b> Approved</li> <li> <b>IPART</b> Approved</li> </ul>
--	--	--	---

## PRODUCT DATA

Order Code	262002
Voltage	220-240V
Wattage	10.5W
Lumen Output	800Lm
CCT	4000K
IP Rating	IP20
Beam Angle	60°
Light Source	SMD Chips
Driver	Remote
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)
Connection	1.2 flex & plug
Construction	Aluminium body / faceted reflector
Fitting Colour	Black
PF	0.9
Net Weight (kg)	0.24
Lifetime L70B50	35,000 hours
Warranty	5 years

## OPTIONAL ACCESSORIES

ITEM	ORDER CODE	ITEM	ORDER CODE
Fixed Holder (White)	292001	Gimbal Holder (Satin Chrome)	292004
Gimbal Holder (White)	292003		



**SUMMARY**

The Emilite is an adjustable modular downlight ideal for commercial and residential applications. Engineered to deliver high lumen efficacy, this downlight features a remote dimmable driver, allowing it to be safely installed under ceiling insulation. The Emilite is required to be installed in conjunction with the Emilite downlight holder. It's also a retrofit solution to traditional GU10 and MR16 style downlights where the existing holder may be used.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	262001
Voltage	220-240V
Wattage	10.5W
Lumen Output	750Lm
CCT	3000K
IP Rating	IP20
Beam Angle	60°
Light Source	SMD Chips
Driver	Remote
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)
Connection	1.2 flex & plug
Construction	Aluminium body / faceted reflector
Fitting Colour	Black
PF	0.9
Net Weight (kg)	0.24
Lifetime L70B50	35,000 hours
Warranty	5 years

**OPTIONAL ACCESSORIES**

ITEM	ORDER CODE	ITEM	ORDER CODE
Fixed Holder (White)	292001	Gimbal Holder (Satin Chrome)	292004
Gimbal Holder (White)	292003		

