

**SUMMARY**

The Legolite is a high performing commercial downlight. Engineered to deliver high lumen efficacy, it features Tri-Colour Selectable technology, giving installers a choice of 3 colour temperatures within 1 fitting for individual preference or application requirements. Incorporating an integrated dimmable driver, it also features Multi-Watt Selectable technology, giving installers a choice of 2 wattages within 1 fitting for maximum lumen output flexibility.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	263007	
Voltage	220-240V	
Wattage	Multi-Watt Selectable	
	12W	8W
Lumen Output 3K	1100Lm	750Lm
Lumen Output 4K & 5K	1200Lm	800Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5K	
IP Rating	IP54	
IC Rating	CA90	
Beam Angle	110°	
Light Source	SMD Chips	
Driver	Integrated	
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)	
Connection	1.2m flex & plug	
Cutout Size	Ø200mm	
Construction	Polycarbonate body / opal polycarbonate diffuser	
Fitting Colour	White	
PF	0.9	
Net Weight (kg)	0.69	
Lifetime L70B50	50,000 hours	
Warranty	5 years	



**SUMMARY**

The Legolite is a high performing commercial downlight. Engineered to deliver high lumen efficacy, it features Tri-Colour Selectable technology, giving installers a choice of 3 colour temperatures within 1 fitting for individual preference or application requirements. Incorporating an integrated dimmable driver, it also features Multi-Watt Selectable technology, giving installers a choice of 2 wattages within 1 fitting for maximum lumen output flexibility.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	263008	
Voltage	220-240V	
Wattage	Multi-Watt Selectable	
	25W	18W
Lumen Output 3K	2150Lm	1650Lm
Lumen Output 4K & 5K	2300Lm	1800Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5K	
IP Rating	IP54	
IC Rating	CA90	
Beam Angle	110°	
Light Source	SMD Chips	
Driver	Integrated	
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)	
Connection	1.2m flex & plug	
Cutout Size	Ø200mm	
Construction	Polycarbonate body / opal polycarbonate diffuser	
Fitting Colour	White	
PF	0.9	
Net Weight (kg)	0.69	
Lifetime L70B50	50,000 hours	
Warranty	5 years	



**SUMMARY**

The Legolite is a high performing commercial downlight. Engineered to deliver high lumen efficacy, it features Tri-Colour Selectable technology, giving installers a choice of 3 colour temperatures within 1 fitting for individual preference or application requirements. Incorporating an integrated dimmable driver, it also features Multi-Watt Selectable technology, giving installers a choice of 2 wattages within 1 fitting for maximum lumen output flexibility.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	263005	
Voltage	220-240V	
Wattage	Multi-Watt Selectable	
	12W	8W
Lumen Output 3K	1100Lm	750Lm
Lumen Output 4K & 5K	1200Lm	800Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5K	
IP Rating	IP54	
IC Rating	CA90	
Beam Angle	110°	
Light Source	SMD Chips	
Driver	Integrated	
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)	
Connection	1.2m flex & plug	
Cutout Size	Ø150mm	
Construction	Polycarbonate body / opal polycarbonate diffuser	
Fitting Colour	White	
PF	0.9	
Net Weight (kg)	0.60	
Lifetime L70B50	50,000 hours	
Warranty	5 years	



**SUMMARY**

The Legolite is a high performing commercial downlight. Engineered to deliver high lumen efficacy, it features Tri-Colour Selectable technology, giving installers a choice of 3 colour temperatures within 1 fitting for individual preference or application requirements. Incorporating an integrated dimmable driver, it also features Multi-Watt Selectable technology, giving installers a choice of 2 wattages within 1 fitting for maximum lumen output flexibility.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	263006	
Voltage	220-240V	
Wattage	Multi-Watt Selectable	
	25W	18W
Lumen Output 3K	2150Lm	1650Lm
Lumen Output 4K & 5K	2300Lm	1800Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5K	
IP Rating	IP54	
IC Rating	CA90	
Beam Angle	110°	
Light Source	SMD Chips	
Driver	Integrated	
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)	
Connection	1.2m flex & plug	
Cutout Size	Ø150mm	
Construction	Polycarbonate body / opal polycarbonate diffuser	
Fitting Colour	White	
PF	0.9	
Net Weight (kg)	0.60	
Lifetime L70B50	50,000 hours	
Warranty	5 years	

