

SUMMARY

The LiteW8 is a versatile floodlight for residential applications. Rated to IP65 and IK08, this floodlight has been engineered to be remarkably light weight for easy handling and installation. It features a UV resistant polycarbonate body with an adjustable angle of support. The LiteW8 incorporates high efficiency SMD LED chips and an integrated driver.



| | | | |
|--|--|--|--|
| | | | <p>✓ VEET Approved</p> <p>✓ IPART Approved</p> |
|--|--|--|--|

PRODUCT DATA

| | |
|-----------------|--|
| Order Code | 273155 |
| Voltage | 220-240V |
| Wattage | 85W |
| Lumen Output | 1000Lm |
| CCT | 5000K |
| IP Rating | IP65 |
| IK Rating | IK08 |
| CRI Rating | Ra≥80 |
| Beam Angle | 100° |
| Light Source | SMD Chips |
| Driver | Integrated |
| Dimmable | No |
| Connection | 1.5m flex & plug |
| Construction | Polycarbonate body / opal polycarbonate diffuser |
| Fitting Colour | Black |
| PF | 0.9 |
| Net Weight (kg) | 1.58 |
| Lifetime L70B50 | 50,000 hours |
| Warranty | 5 years |



SUMMARY

The LiteW8 is a versatile floodlight for residential applications. Rated to IP65 and IK08, this floodlight has been engineered to be remarkably light weight for easy handling and installation. It features a UV resistant polycarbonate body with an adjustable angle of support. The LiteW8 incorporates high efficiency SMD LED chips and an integrated driver.



| | | | |
|--|--|--|--|
| | | | <p>✓ VEET Approved</p> <p>✓ IPART Approved</p> |
|--|--|--|--|

PRODUCT DATA

| | |
|-----------------|--|
| Order Code | 273145 |
| Voltage | 220-240V |
| Wattage | 45W |
| Lumen Output | 5000Lm |
| CCT | 5000K |
| IP Rating | IP65 |
| IK Rating | IK08 |
| CRI Rating | Ra≥80 |
| Beam Angle | 100° |
| Light Source | SMD Chips |
| Driver | Integrated |
| Dimmable | No |
| Connection | 1.5m flex & plug |
| Construction | Polycarbonate body / opal polycarbonate diffuser |
| Fitting Colour | Black |
| PF | 0.9 |
| Net Weight (kg) | 0.68 |
| Lifetime L70B50 | 50,000 hours |
| Warranty | 5 years |



SUMMARY

The LiteW8 is a versatile floodlight for residential applications. Rated to IP65 and IK08, this floodlight has been engineered to be remarkably light weight for easy handling and installation. It features a UV resistant polycarbonate body with an adjustable angle of support. The LiteW8 incorporates high efficiency SMD LED chips and an integrated driver.



| | | | |
|--|--|--|--|
| | | | <p>✓ VEET Approved</p> <p>✓ IPART Approved</p> |
|--|--|--|--|

PRODUCT DATA

| | |
|-----------------|--|
| Order Code | 273135 |
| Voltage | 220-240V |
| Wattage | 24W |
| Lumen Output | 2640Lm |
| CCT | 5000K |
| IP Rating | IP65 |
| IK Rating | IK08 |
| CRI Rating | Ra≥80 |
| Beam Angle | 100° |
| Light Source | SMD Chips |
| Driver | Integrated |
| Dimmable | No |
| Connection | 1.5m flex & plug |
| Construction | Polycarbonate body / opal polycarbonate diffuser |
| Fitting Colour | Black |
| PF | 0.9 |
| Net Weight (kg) | 0.52 |
| Lifetime L70B50 | 50,000 hours |
| Warranty | 5 years |

