

SUMMARY

The MarVelite Pro is a heavy-duty LED floodlight for commercial and industrial applications. Rated IP66 and IK08, this robust luminaire is suitable for harsh outdoor conditions. It features high efficiency SMD chips, die-cast aluminium body and a tempered glass cover. It also features a breather valve for superior heat management and trouble-free operation in the future. Designed to be easily installed, it incorporates an integrated Flicker-Free driver and pre-wired flex and plug. Its mounting arm is also adjustable up to 90°.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	273175
Voltage	220-240V
Wattage	120W
Lumen Output	18200Lm
CCT	5000K
IP Rating	IP66
IK Rating	IK08
CRI Rating	Ra≥80
Beam Angle	110°
Light Source	SMD Chips
Driver	Integrated Flicker-Free
Dimmable	No
Connection	1.5m flex & plug
Construction	Aluminium body / tempered glass cover panel
Fitting Colour	Black
PF	0.9
Net Weight (kg)	3.27
Lifetime L70B50	50,000 hours
Warranty	5 years

- 5000K
- IP66
- IK08
- FLICKER
FREE
- FLEX
& PLUG
- CRI 80
-
- 5 YEAR
WARRANTY



SUMMARY

The MarVelite Pro is a heavy-duty LED floodlight for commercial and industrial applications. Rated IP66 and IK08, this robust luminaire is suitable for harsh outdoor conditions. It features high efficiency SMD chips, die-cast aluminium body and a tempered glass cover. It also features a breather valve for superior heat management and trouble-free operation in the future. Designed to be easily installed, it incorporates an integrated Flicker-Free driver and pre-wired flex and plug. Its mounting arm is also adjustable up to 90°.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	273174
Voltage	220-240V
Wattage	120W
Lumen Output	18200Lm
CCT	4000K
IP Rating	IP66
IK Rating	IK08
CRI Rating	Ra≥80
Beam Angle	110°
Light Source	SMD Chips
Driver	Integrated Flicker-Free
Dimmable	No
Connection	1.5m flex & plug
Construction	Aluminium body / tempered glass cover panel
Fitting Colour	Black
PF	0.9
Net Weight (kg)	3.27
Lifetime L70B50	50,000 hours
Warranty	5 years

