

SUMMARY

The Protail is a high performing commercial downlight. Rated to UGR<19, it features low-glare characteristics for improved lighting comfort. The Protail incorporates an aluminium heat sink and an integrated driver.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	172410
Voltage	220-240V
Wattage	8W
Lumen Output	800Lm
CCT	4000K
IP Rating	IP20
IC Rating	CA90
UGR Rating	UGR<19
Beam Angle	60°
Light Source	SMD Chips
Driver	Integrated
Dimmable	No
Connection	1.2 flex & plug
Cutout Size	Ø100mm
Construction	Polycarbonate body / faceted reflector
Fitting Colour	White
PF	0.9
Net Weight (kg)	0.28
Lifetime L70B50	50,000 hours
Warranty	5 years



SUMMARY

The Protail is a high performing commercial downlight. Rated to UGR<19, it features low-glare characteristics for improved lighting comfort. The Protail incorporates an aluminium heat sink and an integrated driver.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	172308
Voltage	220-240V
Wattage	8W
Lumen Output	720Lm
CCT	3000K
IP Rating	IP20
IC Rating	CA90
UGR Rating	UGR<19
Beam Angle	60°
Light Source	SMD Chips
Driver	Integrated
Dimmable	No
Connection	1.2 flex & plug
Cutout Size	Ø100mm
Construction	Polycarbonate body / faceted reflector
Fitting Colour	White
PF	0.9
Net Weight (kg)	0.28
Lifetime L70B50	50,000 hours
Warranty	5 years

