

SUMMARY

The Stellar V Wide is an IP20 batten ideal for the retrofit market in commercial and industrial applications. It features Five-Colour selectable and Multi-Watt selectable technologies, giving installers the choice of 5 colour temperatures and 8 wattages in 1 fitting so that fewer varieties are required to meet a broader range of needs. With the installer in mind, the Stellar V has been engineered with a clever toolless end cap and quick-to-fit single piece LED light module. It also incorporates multiple cable entry points and a large 6mm terminal block. The integrated sensor's dimming function can be conveniently controlled from a distance with the compatible remote control - available to order separately.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211026DS							
Voltage	220-240V							
Wattage	Multi-Watt Selectable							
	40W	36W	30W	26W	24W	20W	14W	10W
Lumen Output 3K	3600Lm	3240Lm	2700Lm	2340Lm	2160Lm	1800Lm	1260Lm	900Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	4000Lm	3600Lm	3000Lm	2600Lm	2400Lm	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K							
IP Rating	IP20							
Beam Angle	120°							
Light Source	SMD Chips							
Driver	Integrated							
Dimmable	Yes. 0-10V							
Construction	Metal body / opal polycarbonate diffuser							
Fitting Colour	White							
PF	0.9							
Net Weight (kg)	2.67							
Lifetime L70B50	50,000 hours							
Warranty	5 years							

OPTIONAL ACCESSORIES

ITEM	ORDER CODE
Remote Control	213979



SUMMARY

The Stellar V Wide is an IP20 batten ideal for the retrofit market in commercial and industrial applications. It features Five-Colour selectable and Multi-Watt selectable technologies, giving installers the choice of 5 colour temperatures and 3 wattages in 1 fitting so that fewer varieties are required to meet a broader range of needs. With the installer in mind, the Stellar V has been engineered with a clever toolless end cap and quick-to-fit single piece LED light module. It also incorporates multiple cable entry points and a large 6mm terminal block. The integrated sensor's dimming function can be conveniently controlled from a distance with the compatible remote control - available to order separately.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211025DS		
Voltage	220-240V		
Wattage	Multi-Watt Selectable		
	20W	14W	10W
Lumen Output 3K	1800Lm	1260Lm	900Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K		
IP Rating	IP20		
Beam Angle	120°		
Light Source	SMD Chips		
Driver	Integrated		
Dimmable	Yes. 0-10V		
Construction	Metal body / opal polycarbonate diffuser		
Fitting Colour	White		
PF	0.9		
Net Weight (kg)	1.54		
Lifetime L70B50	50,000 hours		
Warranty	5 years		

OPTIONAL ACCESSORIES

ITEM	ORDER CODE
Remote Control	213979



SUMMARY

The Stellar V Wide is an IP20 batten ideal for the retrofit market in commercial and industrial applications. It features Five-Colour selectable and Multi-Watt selectable technologies, giving installers the choice of 5 colour temperatures and 8 wattages in 1 fitting so that fewer varieties are required to meet a broader range of needs. With the installer in mind, the Stellar V has been engineered with a clever toolless end cap and quick-to-fit single piece LED light module. It also incorporates multiple cable entry points and a large 6mm terminal block.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211026
Voltage	220-240V
Wattage	Multi-Watt Selectable 40W 36W 30W 26W 24W 20W 14W 10W
Lumen Output 3K	3600Lm 3240Lm 2700Lm 2340Lm 2160Lm 1800Lm 1260Lm 900Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	4000Lm 3600Lm 3000Lm 2600Lm 2400Lm 2000Lm 1400Lm 1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K
IP Rating	IP20
Beam Angle	120°
Light Source	SMD Chips
Driver	Integrated Flicker-Free
Dimmable	No
Construction	Metal body / opal polycarbonate diffuser
Fitting Colour	White
PF	0.9
Net Weight (kg)	2.65
Lifetime L70B50	50,000 hours
Warranty	5 years



SUMMARY

The Stellar V Wide is an IP20 batten ideal for the retrofit market in commercial and industrial applications. It features Five-Colour selectable and Multi-Watt selectable technologies, giving installers the choice of 5 colour temperatures and 3 wattages in 1 fitting so that fewer varieties are required to meet a broader range of needs. With the installer in mind, the Stellar V has been engineered with a clever toolless end cap and quick-to-fit single piece LED light module. It also incorporates multiple cable entry points and a large 6mm terminal block.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211025		
Voltage	220-240V		
Wattage	Multi-Watt Selectable		
	20W	14W	10W
Lumen Output 3K	1800Lm	1260Lm	900Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K		
IP Rating	IP20		
Beam Angle	120°		
Light Source	SMD Chips		
Driver	Integrated Flicker-Free		
Dimmable	No		
Construction	Metal body / opal polycarbonate diffuser		
Fitting Colour	White		
PF	0.9		
Net Weight (kg)	1.52		
Lifetime L70B50	50,000 hours		
Warranty	5 years		

