

**SUMMARY**

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 8 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. The integrated sensor's dimming function can be conveniently controlled from a distance with the optionally available remote control.



--	--	--

**PRODUCT DATA**

Order Code	211033DS					
Voltage	220-240V					
Wattage	Multi-Watt Selectable					
	60W	53W	48W	40W	36W	28W
Lumen Output 3K	5580Lm	4929Lm	4464Lm	3720Lm	3348Lm	2604Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	6000Lm	5300Lm	4800Lm	4000Lm	3600Lm	2800Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K					
IP Rating	IP65					
IK Rating	IK08					
Beam Angle	120°					
Light Source	SMD Chips					
Driver	Integrated					
Dimmable	Yes. 0-10V					
Construction	High impact polycarbonate body / opal polycarbonate diffuser					
Fitting Colour	Grey					
PF	0.9					
Net Weight (kg)	2.50					
Lifetime L70B50	50,000 hours					
Warranty	5 years					

**OPTIONAL ACCESSORIES**

ITEM	ORDER CODE	ITEM	ORDER CODE
S316 Stainless Steel Clips	232005	Remote Control	213979



**SUMMARY**

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 5 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module.



--	--	--

**PRODUCT DATA**

Order Code	211033					
Voltage	220-240V					
Wattage	Multi-Watt Selectable					
	60W	53W	48W	40W	36W	28W
Lumen Output 3K	5580Lm	4929Lm	4464Lm	3720Lm	3348Lm	2604Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	6000Lm	5300Lm	4800Lm	4000Lm	3600Lm	2800Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K					
IP Rating	IP65					
IK Rating	IK08					
Beam Angle	120°					
Light Source	SMD Chips					
Driver	Integrated Flicker-Free					
Dimmable	Yes. 0-10V					
Construction	High impact polycarbonate body / opal polycarbonate diffuser					
Fitting Colour	Grey					
PF	0.9					
Net Weight (kg)	2.48					
Lifetime L70B50	50,000 hours					
Warranty	5 years					

**OPTIONAL ACCESSORIES**

ITEM	ORDER CODE
S316 Stainless Steel Clips	232005



### SUMMARY

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 8 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. The integrated sensor's dimming function can be conveniently controlled from a distance with the optionally available remote control.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

### PRODUCT DATA

Order Code	211022DS							
Voltage	220-240V							
Wattage	Multi-Watt Selectable							
	40W	36W	30W	26W	24W	20W	14W	10W
Lumen Output 3K	3720Lm	3348Lm	2790Lm	2418Lm	2232Lm	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	4000Lm	3600Lm	3000Lm	2600Lm	2400Lm	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K							
IP Rating	IP65							
IK Rating	IK08							
Beam Angle	120°							
Light Source	SMD Chips							
Driver	Integrated							
Dimmable	Yes. 0-10V							
Construction	High impact polycarbonate body / opal polycarbonate diffuser							
Fitting Colour	Grey							
PF	0.9							
Net Weight (kg)	2.17							
Lifetime L70B50	50,000 hours							
Warranty	5 years							

### OPTIONAL ACCESSORIES

ITEM	ORDER CODE	ITEM	ORDER CODE
S316 Stainless Steel Clips	232005	Remote Control	213979



**SUMMARY**

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 8 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	211022							
Voltage	220-240V							
Wattage	Multi-Watt Selectable							
	40W	36W	30W	26W	24W	20W	14W	10W
Lumen Output 3K	3720Lm	3348Lm	2790Lm	2418Lm	2232Lm	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	4000Lm	3600Lm	3000Lm	2600Lm	2400Lm	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K							
IP Rating	IP65							
IK Rating	IK08							
Beam Angle	120°							
Light Source	SMD Chips							
Driver	Integrated Flicker-Free							
Dimmable	No							
Construction	High impact polycarbonate body / opal polycarbonate diffuser							
Fitting Colour	Grey							
PF	0.9							
Net Weight (kg)	2.15							
Lifetime L70B50	50,000 hours							
Warranty	5 years							

**OPTIONAL ACCESSORIES**

ITEM	ORDER CODE
S316 Stainless Steel Clips	232005



**SUMMARY**

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 3 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. The integrated sensor's dimming function can be conveniently controlled from a distance with the optionally available remote control.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	211021DS		
Voltage	220-240V		
Wattage	Multi-Watt Selectable		
	20W	14W	10W
Lumen Output 3K	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K		
IP Rating	IP65		
IK Rating	IK08		
Beam Angle	120°		
Light Source	SMD Chips		
Driver	Integrated		
Dimmable	Yes. 0-10V		
Construction	High impact polycarbonate body / opal polycarbonate diffuser		
Fitting Colour	Grey		
PF	0.9		
Net Weight (kg)	1.30		
Lifetime L70B50	50,000 hours		
Warranty	5 years		

**OPTIONAL ACCESSORIES**

ITEM	ORDER CODE	ITEM	ORDER CODE
S316 Stainless Steel Clips	232005	Remote Control	213979





**SUMMARY**

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 3 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module.



			<p>✓ <b>VEET</b> Approved</p> <p>✓ <b>IPART</b> Approved</p>
--	--	--	--

**PRODUCT DATA**

Order Code	211021		
Voltage	220-240V		
Wattage	Multi-Watt Selectable		
	20W	14W	10W
Lumen Output 3K	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K		
IP Rating	IP65		
IK Rating	IK08		
Beam Angle	120°		
Light Source	SMD Chips		
Driver	Integrated Flicker-Free		
Dimmable	No		
Construction	High impact polycarbonate body / opal polycarbonate diffuser		
Fitting Colour	Grey		
PF	0.9		
Net Weight (kg)	1.28		
Lifetime L70B50	50,000 hours		
Warranty	5 years		

**OPTIONAL ACCESSORIES**

ITEM	ORDER CODE
S316 Stainless Steel Clips	232005

