

SUMMARY

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 8 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. Fully approved to AS/NZS-2293, the integrated sensor's dimming function can be conveniently controlled from a distance with the optionally available remote control.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211022DEMS							
Voltage	220-240V							
Wattage	Multi-Watt Selectable							
	40W	36W	30W	26W	24W	20W	14W	10W
Lumen Output 3K	3720Lm	3348Lm	2790Lm	2418Lm	2232Lm	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	4000Lm	3600Lm	3000Lm	2600Lm	2400Lm	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K							
IP Rating	IP65							
IK Rating	IK08							
Beam Angle	120°							
Light Source	SMD Chips							
Driver	Integrated							
Dimmable	Yes. 0-10V							
Construction	High impact polycarbonate body / opal polycarbonate diffuser							
Fitting Colour	Grey							
PF	0.9							
EMG Classification	C0:D63 / C90:D32							
Battery	LiFePO4							
Net Weight (kg)	2.42							
Lifetime L70B50	50,000 hours							
Warranty	3 years							

OPTIONAL ACCESSORIES

ITEM	ORDER CODE	ITEM	ORDER CODE
S316 Stainless Steel Clips	232005	Remote Control	213979



SUMMARY

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 8 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. Fully approved to AS/NZS-2293.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211022EM							
Voltage	220-240V							
Wattage	Multi-Watt Selectable							
	40W	36W	30W	26W	24W	20W	14W	10W
Lumen Output 3K	3720Lm	3348Lm	2790Lm	2418Lm	2232Lm	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	4000Lm	3600Lm	3000Lm	2600Lm	2400Lm	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K							
IP Rating	IP65							
IK Rating	IK08							
Beam Angle	120°							
Light Source	SMD Chips							
Driver	Integrated Flicker-Free							
Dimmable	No							
Construction	High impact polycarbonate body / opal polycarbonate diffuser							
Fitting Colour	Grey							
PF	0.9							
EMG Classification	C0:D63 / C90:D32							
Battery	LiFePO4							
Net Weight (kg)	2.40							
Lifetime L70B50	50,000 hours							
Warranty	3 years							

OPTIONAL ACCESSORIES

ITEM	ORDER CODE
S316 Stainless Steel Clips	232005



SUMMARY

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 3 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. Fully approved to AS/NZS-2293, the integrated sensor's dimming function can be conveniently controlled from a distance with the optionally available remote control.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211021DEMS		
Voltage	220-240V		
Wattage	Multi-Watt Selectable		
	20W	14W	10W
Lumen Output 3K	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K		
IP Rating	IP65		
IK Rating	IK08		
Beam Angle	120°		
Light Source	SMD Chips		
Driver	Integrated		
Dimmable	Yes. 0-10V		
Construction	High impact polycarbonate body / opal polycarbonate diffuser		
Fitting Colour	Grey		
PF	0.9		
EMG Classification	C0:D63 / C90:D32		
Battery	LiFePO4		
Net Weight (kg)	1.62		
Lifetime L70B50	50,000 hours		
Warranty	3 years		

OPTIONAL ACCESSORIES

ITEM	ORDER CODE	ITEM	ORDER CODE
S316 Stainless Steel Clips	232005	Remote Control	213979



SUMMARY

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 3 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. Fully approved to AS/NZS-2293.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	211021EM		
Voltage	220-240V		
Wattage	Multi-Watt Selectable		
	20W	14W	10W
Lumen Output 3K	1860Lm	1302Lm	930Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K		
IP Rating	IP65		
IK Rating	IK08		
Beam Angle	120°		
Light Source	SMD Chips		
Driver	Integrated Flicker-Free		
Dimmable	No		
Construction	High impact polycarbonate body / opal polycarbonate diffuser		
Fitting Colour	Grey		
PF	0.9		
EMG Classification	C0:D63 / C90:D32		
Battery	LiFePO4		
Net Weight (kg)	1.60		
Lifetime L70B50	50,000 hours		
Warranty	3 years		

OPTIONAL ACCESSORIES

ITEM	ORDER CODE
S316 Stainless Steel Clips	232005

