

**SUMMARY**

The Topik is an IP20 batten ideal for industrial and commercial applications. It features Multi-Watt Selectable technology, giving installers a choice of 2 wattages in 1 fitting for maximum lumen output flexibility. Designed to be easily installed, the Topik incorporates clever tool-free end caps and a quick-to-fit one-piece sealed LED light module.



|  |  |  |   |
|--|--|--|---|
|  |  |  | <ul style="list-style-type: none"> <li> <b>VEET</b><br/>Approved</li> <li> <b>IPART</b><br/>Approved</li> <li> <b>HEERS</b><br/>Approved</li> </ul> |
|--|--|--|---|

**PRODUCT DATA**

|                 |  |        |
|-----------------|--|--------|
| Order Code      | 213555                                   |        |
| Voltage         | 220-240V                                 |        |
| Wattage         | Multi-Watt Selectable                    |        |
|                 | 25W                                      | 18W    |
| Lumen Output    | 3000Lm                                   | 2160Lm |
| CCT             | 5000K                                    |        |
| IP Rating       | IP20                                     |        |
| Beam Angle      | 120°                                     |        |
| Light Source    | SMD Chips                                |        |
| Driver          | Integrated                               |        |
| Dimmable        | No                                       |        |
| Construction    | Metal body / opal polycarbonate diffuser |        |
| Fitting Colour  | White                                    |        |
| PF              | 0.9                                      |        |
| Net Weight (kg) | 1.92                                     |        |
| Lifetime L70B50 | 35,000 hours                             |        |
| Warranty        | 3 years                                  |        |



**SUMMARY**

The Topik is an IP20 batten ideal for industrial and commercial applications. It features Multi-Watt Selectable technology, giving installers a choice of 2 wattages in 1 fitting for maximum lumen output flexibility. Designed to be easily installed, the Topik incorporates clever tool-free end caps and a quick-to-fit one-piece sealed LED light module.



|  |  |  |   |
|--|--|--|---|
|  |  |  | <ul style="list-style-type: none"> <li> <b>VEET</b><br/>Approved</li> <li> <b>IPART</b><br/>Approved</li> <li> <b>HEERS</b><br/>Approved</li> </ul> |
|--|--|--|---|

**PRODUCT DATA**

|                 |  |        |
|-----------------|--|--------|
| Order Code      | 213554                                   |        |
| Voltage         | 220-240V                                 |        |
| Wattage         | Multi-Watt Selectable                    |        |
|                 | 25W                                      | 18W    |
| Lumen Output    | 3000Lm                                   | 2160Lm |
| CCT             | 4000K                                    |        |
| IP Rating       | IP20                                     |        |
| Beam Angle      | 120°                                     |        |
| Light Source    | SMD Chips                                |        |
| Driver          | Integrated                               |        |
| Dimmable        | No                                       |        |
| Construction    | Metal body / opal polycarbonate diffuser |        |
| Fitting Colour  | White                                    |        |
| PF              | 0.9                                      |        |
| Net Weight (kg) | 1.92                                     |        |
| Lifetime L70B50 | 35,000 hours                             |        |
| Warranty        | 3 years                                  |        |

