

SUMMARY

The TriValite is a high performing low-profile downlight ideal for commercial and residential applications. Engineered to deliver high lumen efficacy, this downlight features Tri-Colour Selectable technology, giving installers a choice of 3 colour temperatures within 1 fitting for individual preference or application requirements. Incorporating a remote dimmable driver, the TriValite is rated to IC-4 allowing it to be safely installed under ceiling insulation.



			<ul style="list-style-type: none"> ✓ VEET Approved ✓ IPART Approved
--	--	--	---

PRODUCT DATA

Order Code	172083
Voltage	220-240V
Wattage	8W
Lumen Output 3K	750Lm
Lumen Output 4K & 5.7K	800Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5.7K
IP Rating	IP54
IC Rating	IC-4
Beam Angle	100°
Light Source	SMD Chips
Driver	Remote
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)
Connection	1.2 flex & plug
Fitting Type	Flush
Cutout Size	Ø90mm
Construction	Polycarbonate body / opal polycarbonate diffuser
Fitting Colour	White
PF	0.9
Net Weight (kg)	0.24
Lifetime L70B50	35,000 hours
Warranty	5 years

SUMMARY

The TriValite is a high performing low-profile downlight ideal for commercial and residential applications. Engineered to deliver high lumen efficacy, this downlight features Tri-Colour Selectable technology, giving installers a choice of 3 colour temperatures within 1 fitting for individual preference or application requirements. Incorporating a remote dimmable driver, the TriValite is rated to IC-4 allowing it to be safely installed under ceiling insulation.



			<ul style="list-style-type: none"> ✓ VEET Approved ✓ IPART Approved
--	--	--	---

PRODUCT DATA

Order Code	172083BK
Voltage	220-240V
Wattage	8W
Lumen Output 3K	750Lm
Lumen Output 4K & 5.7K	800Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5.7K
IP Rating	IP54
IC Rating	IC-4
Beam Angle	100°
Light Source	SMD Chips
Driver	Remote
Dimmable	Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List)
Connection	1.2 flex & plug
Fitting Type	Flush
Cutout Size	Ø90mm
Construction	Polycarbonate body / opal polycarbonate diffuser
Fitting Colour	Black
PF	0.9
Net Weight (kg)	0.24
Lifetime L70B50	35,000 hours
Warranty	5 years