Data Sheet



Last modification 2022-11-06

MDL-16D-16W-930 9329501052976



MODULE 16-16w w/TWIST-ON SYST 16watt DIMMABLE wIth lead&plug 3000K 1280Lm Ra>92 38d

Overview

Family name Module
Categories Downlights
Mounting Recess

Usage Indoor Lighting,Trade Selection

Color / Material

Fixture Color

Fixture Material

Diffuser Material

Diffuser Color

Cable Color

Cable Material

Plastic

Clear

Clear

Cable Material

PVC

Size

Fixture Diameter (cm) 5.0 Fixture Height (cm) 7.5

Specification

Voltage Input 240V Wattage (max) 16

Globe Type LED integrated COB

Globe / Light Source qty 1 Globe / Light Source included Yes Lumens 1280 **Color Temperature** Warm White 3000k **Color Kelvin** >92 **Color Rendering Dimmable** Yes **Power Factor** >0.95

All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000. NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

Data Sheet



Surge Protection Yes Beam Angle (degree) 38 **Current Output** 350 **Insulation class** IC-F IP rating IP44 Lead and Plug Yes **Approvals** RCM **Box Contents** Instruction

Installation Required Yes (by Licensed Electrician only)

Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth

Replacement Warranty *5 Years

<u>Barcode</u>

GTIN 9329501052976

Image -dimensions

