

- Ideal for industrial and commercial area lighting.



FEATURES

- Die-cast aluminium body
- Tempered glass
- IP66 weatherproof and IK06 vandal-proof
- High performance aluminium reflector
- Angle of support is adjustable up to 90°
- Fitting colour: Black

INCLUDES

- LED floodlight with driver
- 1.5 m flex and 3 pin plug

APPLICATIONS

- Parks
- Car parks
- Gardens
- Sports center
- Industrial
- Commercial

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
						 0.25kg at 405mm

Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Lumen/W	Beam Angle	Lifetime L70B50	Net Weight (kg)
272406A	YKFLA3S-75W	200-240V	75W	0.9	4000K	10000lm	135lm/W	110°	50000h	3.35
272407A	YKFLA3S-95W	200-240V	95W	0.9	4000K	12800lm	135lm/W	110°	50000h	4.32
272409A	YKFLA3S-110W	200-240V	110W	0.9	4000K	14850lm	135lm/W	110°	50000h	4.32
272410A	YKFLA3S-135W	200-240V	135W	0.9	4000K	18200lm	135lm/W	110°	50000h	5.50
272408A	YKFLA3S-200W	200-240V	200W	0.9	4000K	27000lm	135lm/W	110°	50000h	6.10
272510	YKFLA3S-75W	200-240V	75W	0.9	5000K	10000lm	135lm/W	110°	50000h	3.35
272511	YKFLA3S-95W	200-240V	95W	0.9	5000K	12800lm	135lm/W	110°	50000h	4.32
272513	YKFLA3S-110W	200-240V	110W	0.9	5000K	14850lm	135lm/W	110°	50000h	4.32
272514	YKFLA3S-135W	200-240V	135W	0.9	5000K	18200lm	135lm/W	110°	50000h	5.50
272512	YKFLA3S-200W	200-240V	200W	0.9	5000K	27000lm	135lm/W	110°	50000h	6.10

Part No.	L1 (mm)	W (mm)	H2 (mm)	A1 (mm)	A2 (mm)	Weight (Kg)	VEET Status	IPART Status
272406A 272510	300	245	91	90	150	3.5	Approved No.: 4890	Approved No.: 24143S14-GDEAJIFF
272407A 272511	345	295	91	90	150	4.5	Approved No.: 4890	Approved No.: 24143S14-GDEAJIFF
272409A 272513	345	295	91	90	150	4.5	Approved No.: 4890	Approved No.: 24143S14-GDEAJIFF
272410A 272514	365	330	91	180	240	5.5	Approved No.: 4890	Approved No.: 24143S14-GDEAJIFF
272408A 272512	400	360	91	180	240	6.4	Approved No.: 4890	Approved No.: 24143S14-GDEAJIFF

[1] Operating Frequency=50/60Hz; [2] Operating Temperature:-30 C~+50 C

Specifications are for reference only and may be changed without prior notification.

Version: V4.1 Date: 19/07/2018

