

Installation Locations:

Indoor and outdoor (provided the fan is fully undercover)

Standard Canopy Cover:

Suitable for flat ceilings

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Wall Controller Speed Capacitor Values:

Top of canopy cover to lowest point of the fan:

Approximately 305mm

Rotational Diameter:

1320mm (52") blade sweep

Ceiling to top side of the blade:

280mm

Motor:

157mm x 10mm DC motor

Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and Packaging Dimensions (mm): long life.

Weight Including Packaging:

Complete fan: 6.7kg

Motor Housing:

Materials: ABS Polymer

Complete Fan: 590L x 290W x 310H

Available Motor Housing Colours:

Matt White and Matt Black

Accessories (Supplied separately):

Extension Down Rod 26mm diameter (includes wire harness)

38° Ceiling Kit (for pitched ceilings)

T-Hook for ceiling roses 240V DC Wall Controller

Blades:

Sizes: 1320mm (52") Materials: Polymer Blades

Available Blade Colours:

Blade Pitch: 14°

Warrantv:

2 years in-home warranty on all electric components (control modules, remote control system, lighting and

accessory wall control)

3 years standard "in home" warranty

3 years extended warranty on motor only (excluding

labour)

Matt White. Matt Black and Koa

Extra Information:

Introduced into the HPI range in 2019

6 speed remote controller

Reversible

Airflow CMH:

14,425 on High Speed (Speed 6)

	Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6
RPMS	81	107	145	190	204	214
WATTS	3	5	9	19	22	26