

NO UV/IR

## PARK-120-WG-EM Emergency LED Batten

## Description

The PARK LED Batten series is a direct replacement to traditional T8 and T5 Wide Body Fluorescent battens. The PARK Series LED Batten also features a dual Wattage option. So, if the area is too bright, simply press the switch located on the LED Driver to reduce the light output by half. Pressed body is constructed from high-quality sheet metal, white powder coated with a choice of prismatic polycarbonate diffuser, or wire guard. Available in 600mm and 1200mm lengths, with TRIO, the added option of changing the colour temperature output of the LED batten with a dip switch located inside the fitting. Tricolour switchable LED Colour temperatures - Warm White 3000K, Neutral White 4000K, and White 5000K. Also available as part of a family of ON/OFF and DIM Sensor models as well as Emergency models. Suitable for domestic applications such as laundries, garage, storerooms. Also commercially for underground carparks.

(<mark>3yr</mark>

5yr

ies

20

LED

	0	
Specification Fe	atures	Trio
Designed:	Australian Designed for quick and easy installation	Dip Switch Technology
Input Voltage:	240V AC	
Lumens:	130lm/W high output Dedicated LED	
Wattage:	15W/30W	3 colours
	Half power switch on the driver which decreases the lumen output by 50%	
CCT:	SMD 3000K, 4000K, 5000K (Switchable)	
CRI	≥80	
Beam angle (°):	120°	
Dimmable:	No	ESCAPE
Emergency:	Maintained / Non-Maintained	Emergency Systems
Battery:	LiFePO4	
Cover:	Opal diffuser with even light output	
Terminal:	Large Terminal, PA16	
Approval:	Complies with AS2293.3- 2005+ AMD 1&2 Annex C / EMC compliant	
Feature:	20mm Knockouts for conduit or cable glands, Charge time 24 Hours	
Options:	Optional Internal Microwave Sensor options available — ON/OFF and	
	DIM Sensor options.Setup Remote required for multiple setups to alter	
	default settings to achieve different modes (not supplied)	
Warranty:	5 Year Warranty / 3 Year Warranty on battery	Internal ON/Off Sensor
Diagrams / Ada	litional	
	*****	

						6	
le Dimmable Sensor							
82mm			Item No.	Non-Dim	Variant ON/OFF Sensor*	DIM Sensor*	CCT
×			PARK-120-WG-EM	66083	66084	66085	TRIO
109mm	ed						

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com.au Specification subject to change without prior notice.