

NO UV/IR

PARK-60-DIFF LED Batten

Description

The PARK LED Batten series is a direct replacement to traditional T8 and T5 Wide Body Fluorescent battens. The PARK Series LED Batten also features a dual Wattage option. So, if the area is too bright, simply press the switch located on the LED Driver to reduce the light output by half. Pressed body is constructed from high-quality sheet metal, white powder coated with a choice of prismatic polycarbonate diffuser, or wire guard. Available in 600mm and 1200mm lengths, with TRIO, the added option of changing the colour temperature output of the LED batten with a dip switch located inside the fitting. Tricolour switchable LED Colour temperatures - Warm White 3000K, Neutral White 4000K, and White 5000K. Also available as part of a family of ON/OFF and DIM Sensor models as well as Emergency models. Suitable for domestic applications such as laundries, garage, storerooms. Also commercially for underground carparks.

7.5 /15

5yr

ies

20

LED

Specification Features	
Designed:	Australian Designed for quick and easy installation 3 colours
Input Voltage:	240V AC
Lumens:	130lm/W high output Dedicated LED
Wattage:	7.5W/15W
	Half power switch on the driver which decreases the lumen output by 50%
CCT:	SMD 3000K, 4000K, 5000K (Switchable)
CRI	≥80
Beam angle (°):	120°
Dimmable:	No
Cover:	Opal diffuser with even light output
Terminal:	Large Terminal, PA16
Approval:	Complies with AS2293.3- 2005+ AMD 1&2 Annex C / EMC compliant
Feature:	20mm Knockouts for conduit or cable glands
Options:	Optional Internal Microwave Sensor options available — ON/OFF and
	DIM Sensor options.Setup Remote required for multiple setups to alter
	default settings to achieve different modes (not supplied)
Warranty:	5 Year Warranty
	Item No. <u>Variant</u> CCT



Internal ON/Off Sensor

Dimmable Sensor

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com.au Specification subject to change without prior notice.