

Last modification 2022-11-23

**ROSARIO OY40-CL**  
**9329501054833**



The ROSARIO oyster utilizes state of the art LED lighting to create a contemporary modern style. The domed starlight diffuser evenly dispenses the illumination and is encased by a clear or smoke ribbed deco trim. The universal style complements a range of interior spaces. CCT changeable by internal slide switch, this simple oyster will light your space with a streamlined beauty.

## Overview

<b>Family name</b>	Rosario
<b>Categories</b>	Oysters
<b>Mounting</b>	Surface
<b>This item includes</b>	Diffuser
<b>Usage</b>	Indoor Lighting,Trade Selection

## Color / Material

<b>Fixture Color</b>	Clear,White
<b>Fixture Material</b>	Plastic,Metal,Polycarbonate
<b>Canopy Color</b>	White
<b>Shade Color</b>	Clear
<b>Shade Material</b>	Plastic
<b>Diffuser Color</b>	Starlight,White
<b>Diffuser Material</b>	Polycarbonate

## Size

<b>Fixture Diameter (cm)</b>	40.0
<b>Fixture Height (cm)</b>	6.5
<b>Fixture Projection (cm)</b>	5.0
<b>Canopy Diameter (cm)</b>	35.5
<b>Diffuser Diameter (cm)</b>	40.0

## Specification

<b>Voltage Input</b>	240V
<b>Wattage (max)</b>	30
<b>Globe Type</b>	LED integrated SMD
<b>Globe / Light Source qty</b>	1


All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.  
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

<b>Globe / Light Source included</b>	Yes
<b>Lumens</b>	2400
<b>Color Temperature</b>	Warm White; Natural White; Cool White
<b>Color Kelvin</b>	3 CCT (3000k - 4000k - 5500k)
<b>Color Rendering</b>	>84
<b>Dimmable</b>	Yes - TRIAC
<b>Power Factor</b>	>0.90
<b>Surge Protection</b>	Yes (1.5 Kva)
<b>Electrical Protection</b>	CLASS I - HIGH VOLTAGE, EARTH REQUIRED
<b>IP rating</b>	IP20
<b>Lead and Plug</b>	No
<b>Approvals</b>	RCM
<b>Assembly Required</b>	No
<b>Box Contents</b>	Basic mounting screws,Instruction
<b>Installation Required</b>	Yes (by Licensed Electrician only)
<b>Care Instructions</b>	Do not use strong liquid cleaners,Wipe clean with a dry cloth
<b>Replacement Warranty</b>	*3 Years

## Barcode

**GTIN** 9329501054833

## Image -dimensions





Last modification 2022-11-23

**ROSARIO OY40-SM**  
**9329501054840**



The ROSARIO oyster utilizes state of the art LED lighting to create a contemporary modern style. The domed starlight diffuser evenly dispenses the illumination and is encased by a clear or smoke ribbed deco trim. The universal style complements a range of interior spaces. CCT changeable by internal slide switch, this simple oyster will light your space with a streamlined beauty.

## Overview

<b>Family name</b>	Rosario
<b>Categories</b>	Oysters
<b>Mounting</b>	Surface
<b>This item includes</b>	Diffuser
<b>Usage</b>	Indoor Lighting,Trade Selection

## Color / Material

<b>Fixture Color</b>	White,Smoke
<b>Fixture Material</b>	Plastic,Metal,Polycarbonate
<b>Canopy Color</b>	White
<b>Shade Color</b>	Smoke
<b>Shade Material</b>	Plastic
<b>Diffuser Color</b>	Starlight,White
<b>Diffuser Material</b>	Polycarbonate

## Size

<b>Fixture Diameter (cm)</b>	40.0
<b>Fixture Height (cm)</b>	6.5
<b>Fixture Projection (cm)</b>	5.0
<b>Canopy Diameter (cm)</b>	35.5
<b>Diffuser Diameter (cm)</b>	40.0

## Specification

<b>Voltage Input</b>	240V
<b>Wattage (max)</b>	30
<b>Globe Type</b>	LED integrated SMD
<b>Globe / Light Source qty</b>	1

All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.  
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

<b>Globe / Light Source included</b>	Yes
<b>Lumens</b>	2400
<b>Color Temperature</b>	Warm White; Natural White; Cool White
<b>Color Kelvin</b>	3 CCT (3000k - 4000k - 5500k)
<b>Color Rendering</b>	>84
<b>Dimmable</b>	Yes - TRIAC
<b>Power Factor</b>	>0.90
<b>Surge Protection</b>	Yes (1.5 Kva)
<b>Electrical Protection</b>	CLASS I - HIGH VOLTAGE, EARTH REQUIRED
<b>IP rating</b>	IP20
<b>Lead and Plug</b>	No
<b>Approvals</b>	RCM
<b>Assembly Required</b>	No
<b>Box Contents</b>	Basic mounting screws,Instruction
<b>Installation Required</b>	Yes (by Licensed Electrician only)
<b>Care Instructions</b>	Do not use strong liquid cleaners,Wipe clean with a dry cloth
<b>Replacement Warranty</b>	*3 Years

## Barcode

**GTIN** 9329501054840

## Image -dimensions

