

- Robust circular bulkhead .



### FEATURES

- Die-cast aluminium body
- Built-in high efficiency SMD chips
- Constant current driver fitted
- Opal polycarbonate diffuser
- IP65 weatherproof and IK10 vandal-proof
- Large 6mm terminal block for easy installation
- Fitting colour: Black

### INCLUDES

- LED bunker with driver
- Mounting accessories

### INSTALLATION OPTIONS

- Surface mounted

### APPLICATIONS

- Walkways
- Hallways
- Balconies
- Industrial
- Commercial

### WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
		 Non dim	 Ra≥80			 IK10 5kg at 405mm

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Net Weight (kg)
282010	100-240V	9W	0.9	3000K	600lm	110°	50000h	1.28
282011	100-240V	9W	0.9	4000K	650lm	110°	50000h	1.28
282012	100-240V	9W	0.9	5000K	650lm	110°	50000h	1.28
282013	100-240V	18W	0.9	3000K	1350lm	110°	50000h	2.03
282014	100-240V	18W	0.9	4000K	1450lm	110°	50000h	2.03
282015	100-240V	18W	0.9	5000K	1450lm	110°	50000h	2.03

Part No.	Model No.	VEET Status	IPART Status
282010 282011 282012	YKBHEB3-9W	Approved No.: 4781	Approved No.:24143S13-KJJGYFD
282013 282014 282015	YKBHEB3-18W	Approved No.: 4781	Approved No.:24143S13-KJJGYFD

[1] Operating Frequency=50/60Hz;

[2] Switch Times≥25000;

[3] Operating Temperature:-30 °C~+50 °C

