

# SLICKTRI

LED Dimmable **ULTRA SLIM** Recessed Downlights

**TRI-CCT** 3000K 4000K 5000K

- Input voltage range: 220-240V
- Remote constant current driver included
- Housing & faceplate: PC
- Diffuser: white PS
- Tri-CCT (3000K/ 4000K/ 5000K) in one fitting
- CCT switch on DC cable
- LED chips: SMD2835
- Power factor: 0.9
- CRI: >80
- Flex & plug: 1.2m
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Suitable for use with Microwave & motion sensor




General Lighting


		<b>IP40</b> Rated		
--	--	----------------------	--	--

### Tested & Recommended Dimmers:


BRAND	PART NO.	PCS PER DIMMER
CLA	VELA	
CLIPSAL	32E450UDM, 31E2PUDM, 32ELEDDM-WE, 32E450TM, PDL354PBDMUN-VW	SLICKTRI1R: 2-11PCS SLICKTRI2R: 2-8PCS SLICKTRI3R: 2-5PCS SLICKTRI1S: 2-11PCS SLICKTRI2S: 2-8PCS SLICKTRI3S: 2-5PCS
HPM	Cat 250T, Cat 400T	
Dignet	MEDM, MMDM/RT	




**SLICKTRI1R**




**SLICKTRI1S**




**SLICKTRI2R**



**SLICKTRI2S**



**SLICKTRI3R**



**SLICKTRI3S**

PART NO.	DESCRIPTION	LUMENS			WATT	CRI	BOX WEIGHT	BOX DIMENSIONS	CARTON QTY
		3000K	4000K	5000K					
SLICKTRI1R	D/L LED FIXED DIMM SLIM WH RND TRI	630LM	720LM	680LM	9W	>80	0.31kg	19x45x16cm	1/40
SLICKTRI2R	D/L LED FIXED DIMM SLIM WH RND TRI	840LM	960LM	900LM	12W	>80	0.38kg	19x45x18.5cm	1/40
SLICKTRI3R	D/L LED FIXED DIMM SLIM WH RND TRI	1350LM	1550LM	1450LM	18W	>80	0.5kg	25.5x45x23.5cm	1/20
SLICKTRI1S	D/L LED FIXED DIMM SLIM WH SQ TRI	630LM	720LM	680LM	9W	>80	0.34kg	21x45x16cm	1/40
SLICKTRI2S	D/L LED FIXED DIMM SLIM WH SQ TRI	840LM	960LM	900LM	12W	>80	0.4kg	23x45x18.5cm	1/40
SLICKTRI3S	D/L LED FIXED DIMM SLIM WH SQ TRI	1350LM	1550LM	1450LM	18W	>80	0.6kg	28x45x23.5cm	1/20