



FEATURES

- Energy efficient alternative to fluorescent tubes
- Compatible with main supply
- High efficient SMD chips
- Fully integrated flicker free driver
- Opal glass diffuser
- Fixed G5 cap
- Non dimmable
- Single end power input

APPLICATIONS

- Retail
- Offices
- Stations
- Garages and car parks
- Industrial
- Commercial

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
	 Non dim	 Ra≥80		1463mm(5ft) 26/34W 1163mm(4ft) 16W 563mm(2ft) 7.5W Tube Ø26mm

Part No.	Order Code	Model No.	Voltage	Watt.	PF	Color Temp.	Cap	Lumens	Beam Angle	Lifetime L70B50
363044	363044	T5BNG1-SHLP-FRF-2ft 7.5W	220-240V	7.5W	0.9	4000K	G5	1100lm	230°	50000h
363045	363045	T5BNG1-SHLP-FRF-2ft 7.5W	220-240V	7.5W	0.9	5000K	G5	1100lm	230°	50000h
363054	363054	T5BNG1-SHLP-FRF-4ft 16W	220-240V	16W	0.9	4000K	G5	2400lm	230°	50000h
363055	363055	T5BNG1-SHLP-FRF-4ft 16W	220-240V	16W	0.9	5000K	G5	2400lm	230°	50000h
363074	363074	T5BNG1-SHLP-FRF-5ft 26W	220-240V	26W	0.9	4000K	G5	3900lm	230°	50000h
363075	363075	T5BNG1-SHLP-FRF-5ft 26W	220-240V	26W	0.9	5000K	G5	3900lm	230°	50000h
363034	363034	T5BNG1-SHLP-FRF-5ft 34W	220-240V	34W	0.9	4000K	G5	5100lm	230°	50000h
363035	363035	T5BNG1-SHLP-FRF-5ft 34W	220-240V	34W	0.9	5000K	G5	5100lm	230°	50000h

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+45 °C

*Some luminaires may need to be rewired for the lamps to operate.

Please follow instructions supplied with product.

