



i-Series

**SOLO / DUO / TRIO / QUARTET**

Elegant • Intelligent • Powerful



High Performance  
Micro-Controllers



Customisable  
LED Colours



Solid State  
Relays



Capacitive  
Touch Buttons



Temperature &  
Humidity Sensors



Device Lock  
Function



Removable  
Magnetic Cover



**KEY FEATURES**

- One Button for On/Off & Dimming
- No Neutral wire required\*
- Temperature & Humidity Sensors
- Power Consumption Monitoring
- Capacitive Touch Buttons
- LED Timer Indicator
- Device Lock Function with a 4-digit key
- Customisable Multi-colour Interface
- Adjustable Interface Brightness
- Night Light Mode
- Removable Magnetic Cover
- Fire Resistant Plastics
- Awards Winning Design



**TECHNICAL SPECIFICATIONS**

	<b>SOLO - DUO - TRIO - QUARTET</b>
Connectivity	WiFi 2.4GHz
Channels	SOLO (1) - DUO (2) - TRIO (3) - QUARTET (4)
Customisable LED Illumination	●
Device Lock	●
LED Timer Indicator	●
Temperature Sensor	●
Humidity Sensor	●
Power Consumption Sensor	●
Operating Temperature	-20°C - 45°C
Operating Humidity	0% - 90% RH
Operating Voltage	90V~ - 250V~   50/60Hz
Wattage Rating	300W / Channel
Voltage Measurement Accuracy	±5%
Current Measurement Accuracy	±2% above 0.5A
Temperature Measurement Accuracy	±2%
Humidity Measurement Accuracy	±10% RH

\* Without a neutral wire there is a Minimum Load Requirement per channel.

<b>SOLO</b>	
	<b>22W</b>

<b>DUO</b>	
All channels connected	<b>15W</b>
One channel connected	<b>29W</b>

<b>TRIO</b>	
All channels connected	<b>16W</b>
One channel connected	<b>47W</b>

<b>QUARTET</b>	
All channels connected	<b>15W</b>
One channel connected	<b>64W</b>