

i-Series **DUET & DUET+**

Ingenious • Intuitive • Incredible



High Performance
Micro-Controllers



Customisable
LED Colours



2500 Watts
Per Outlet



Capacitive
Touch Buttons



Temperature &
Humidity Sensors



Device Lock
Function



Smart Active
Technology



KEY FEATURES

- Smart Active™ Technology
- Temperature & Humidity Sensors
- Power Consumption Monitoring
- Capacitive Touch Buttons
- LED Timer Indicator
- Device Lock Function with a 4-digit key
- Customisable Multi-colour Interface
- Adjustable Interface Brightness
- Night Light Mode
- Auxiliary Channel*
- Removable Magnetic Cover
- Fire Resistant Plastics
- Awards Winning Design



* Auxiliary channel is only available on the DUET+ models

TECHNICAL SPECIFICATIONS

	DUET [PP02-1019AN]	DUET+ [PP03-1019AN]
Connectivity	WiFi 2.4GHz	WiFi 2.4GHz
Auxiliary Channel		●
Smart Active Technology	●	●
Customisable LED Illumination	●	●
Device Hardware Lock	●	●
LED Timer Indicator	●	●
Temperature Sensor	●	●
Humidity Sensor	●	●
Power Consumption Sensor	●	●
Operating Temperature	-20°C - 45°C	-20°C - 45°C
Operating Humidity	0% - 90% RH (Non-condensing)	0% - 90% RH (Non-condensing)
Operating Voltage	90V~ - 250V~	90V~ - 250V~
Current Rating	10A per Socket	10A per Socket
Voltage Measurement Accuracy	±5%	±5%
Current Measurement Accuracy	±2% above 0.5A	±2% above 0.5A
Temperature Measurement Accuracy	±2%	±2%
Humidity Measurement Accuracy	±10% RH	±10% RH