

TYPHOON MACH 3 56" CEILING FAN



White

Installation Locations:

Indoor Only

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan:

Approximately 340mm

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 32°

Wall Controller Speed Capacitor Values:

4.5µF & 2.5µF

Rotational Diameter:

1420mm (56") Blade Sweep

Motor:

16 Pole, 194 x 16mm Motor

Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Weight Including Packaging:

Complete fan 1420mm: 7.6kg

Packaging Dimensions (cm):

Complete fan 1420mm: 71L x 23W x 27H

Motor Housing:

Materials: Pressed Steel (Painted, Plated or Powder Coated Finish)

Accessories (Supplied separately):

Remote Control
Extension Down Rod 21mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses

Available Motor Housing Colours :

White, Brushed Chrome, Matt Black

Blades:

Sizes:1420mm
Materials: Aluminium
Blade Pitch: 18°

Warranty

2 year standard "in home" warranty
3 years extended warranty on motor only (excluding labour)

Available Blade Colours:

White, Brushed Chrome, Matt Black

Extra Information:

Introduced into the HPI range in 2017, 3 Speed wall controller, Light Adaptable, Reversible.

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

Maintenance:

When used in areas of high humidity regular cleaning is required (4-6 times per year).

<i>Typhoon Mach 3 1420mm (56")</i>	HIGH	MED	LOW
RPMS	238	148	100
WATTS	73	38	20
AIRFLOW: CFM* / CMH*	9450 / 16050	5340 / 9070	3008 / 5110
EFFICIENCY^: (CFM / Watt) / (CMH / Watt)	129 / 220	141 / 239	150 / 256

* CFM = Cubic Feet per Minute / CMH = Cubic Meters per Hour.


^ Efficiency measured as airflow rate per Watt.

TYPHOON MACH 3 CEILING FAN ACCESSORY LIGHTING




! Light kit must be installed by a licensed electrician

E27 Light (MAX 2x42W)



- Accepts a variety of lamps, e.g. incandescent, fluorescent.**
- Cost effective



ECLIPSE STYLE GLASS



Colours Available:

All light kits are available in most motor colours ~ White, Brushed Chrome, Matt Black.

Packaging Dimensions

15H x 25W x 25L

Weight

1.5 kg

** Compact fluorescent lamps vary in size and must not touch the glass diffuser.

Note: Use of incandescent lamps may cause corrosion to occur on parts of the light when used in very humid environments.

^ All light kits must be installed by a licensed electrician. For further information about correct installation procedures, please see www.hunterpacific.com.au

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au