



### FEATURES

- Plastic downlight module with internal aluminium heat sink
- High efficiency SMD LED chips
- Easy installation
- IC-4 rating. Can be installed under ceiling insulation
- Opal polycarbonate diffuser
- Adjust the color temperature
- App control. Bluetooth 5.0
- Work with Amazon Alexa and Google Assistant

### INCLUDES

- Dimmable LED driver
- 1.2 m flex and plug

### APPLICATIONS

- Residential
- Hotels and shops
- Conference rooms
- Reception areas
- Bathrooms and wet areas

### WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION		IP RATING	DIMMABLE	Ra	DISTRIBUTION

Part No.	Order Code	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Diffuser	Net Weight (kg)
173290	173290	RS3A1-WBLE 8W	220-240V	8W	0.5	2200-6500K	33-800lm	100°	35000h	Flush	0.24
173300	173300	RS3B1-WBLE 8W	220-240V	8W	0.5	2200-6500K	33-800lm	100°	35000h	Recessed	0.24

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C ~+40 °C

[3] Connection performance may vary when connection quantity over 50 pieces

