

- Selectable power, selectable colour temperature, easy installation bunker.



Flicker Free



Microwave motion sensor kits



Sustained emergency kits (LiFePO4 Battery)



Eyelid cover-Black



Eyelid cover-White

FEATURES

- Corrosion free UV resistant tough polycarbonate enclosure
- Built-in high efficiency SMD LED chips
- Switchable tri-power and tri-colour selection
- Large 6mm terminal block and centred cable entry for easy installation
- Rear / side cable entry available
- Compatible with 51mm Beza box
- Plug and play modular sensor and emergency kit install on-site
- Eyelid cover options available

INCLUDES

- LED bunker with driver
- Mounting accessories
- Fast connector

INSTALLATION OPTIONS

- Surface mounted installation

APPLICATIONS

- Walkways
- Hallways
- Balconies
- Commercial
- Industrial

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	TRI-COLOUR	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING

Part No.	Order Code	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Net Weight (kg)
281003	281003	BHD1-TC-D3022MN 10W	220-240V	10W	0.9	3000K/4000K/5000K	930/1000/1000lm	110°	50000h	0.82
		BHD1-TC-D3022MN 15W	220-240V	15W	0.9	3000K/4000K/5000K	1400/1500/1500lm	110°	50000h	0.82
		BHD1-TC-D3022MN 22W	220-240V	22W	0.9	3000K/4000K/5000K	1860/2000/2000lm	110°	50000h	0.82
281004	281004	BHD1-TC-D3022MN 10W	220-240V	10W	0.9	3000K/4000K/5000K	930/1000/1000lm	110°	50000h	0.82
		BHD1-TC-D3022MN 15W	220-240V	15W	0.9	3000K/4000K/5000K	1400/1500/1500lm	110°	50000h	0.82
		BHD1-TC-D3022MN 22W	220-240V	22W	0.9	3000K/4000K/5000K	1860/2000/2000lm	110°	50000h	0.82

[1] Operating Frequency=50/60Hz; [2] Operating Temperature:-30 C ~+50 C

Accessories (Optional)

Part No.	Order Code	Model No.	Note
283039	283039	ECD1BH BK	Unit LED bunker eyelid cover black
283099	283099	ECD1BH WH	Unit LED bunker eyelid cover white
283049	283049	MA1EN04W005-L11W08	Sustained emergency kits
283059	283059	ECMMSB1	Microwave motion sensor kits