




## 167 - CCT Downlight

### Product Specifications

<b>SKU</b>	VBLDL-167-1-CCT
<b>Luminaire efficacy</b>	70 lm/W
<b>Product Series</b>	VBLDL-167-SERIES
<b>EAN</b>	9340994020891
<b>Wattage</b>	10 W
<b>Lumen output</b>	700 lm
<b>IP rating</b>	65
<b>Beam Angle</b>	60 Degrees
<b>Trim colour</b>	White
<b>Cut out</b>	70 mm
<b>Lifespan</b>	50000 Hours
<b>Warranty</b>	3 Years
<b>Mounting type</b>	Recessed
<b>Wiring method</b>	Flex & Plug
<b>Dimming</b>	Triac Dimming
<b>Input voltage</b>	220V-240V AC 50HZ
<b>Working temperature</b>	-20°C~ 45°C



### Dimensional Drawings



*Photometric information available upon request.*



## 167 - WIZ SMART Downlight

### Product Specifications

<b>SKU</b>	VBLDL-167-1-WIZ
<b>Luminaire efficacy</b>	70 lm/W
<b>Product Series</b>	VBLDL-167-SERIES
<b>EAN</b>	9340994021232
<b>Wattage</b>	10 W
<b>Lumen output</b>	700 lm
<b>IP rating</b>	65
<b>IK Rating</b>	8
<b>CRI</b>	80
<b>Beam Angle</b>	60 Degrees
<b>Trim colour</b>	White
<b>Cut out</b>	70 mm
<b>Lifespan</b>	50000 Hours
<b>Warranty</b>	3 Years
<b>Mounting type</b>	Recessed
<b>Wiring method</b>	Flex & Plug
<b>Dimming</b>	Triac Dimming
<b>Constant current/voltage</b>	Constant Current
<b>Lamp Type</b>	LED
<b>Input voltage</b>	100V - 240V AC
<b>Working temperature</b>	-20°C ~ 45°C



*Photometric information available upon request.*