



## LED DOWNLT 3K/4K CCT MUST ADD DRIVER 14W/20W/30W

### Product Specifications

<b>SKU</b>	VBLDL-436A-1-CCT
<b>Luminaire efficacy</b>	105 lm/W
<b>Product Series</b>	VBLDL-4X6-SERIES
<b>EAN</b>	9340994022307
<b>Wattage</b>	20 W
<b>Lumen output</b>	2100 lm
<b>IP rating</b>	54
<b>CRI</b>	90
<b>Beam Angle</b>	85 Degrees
<b>Trim colour</b>	White
<b>Cut out</b>	175 mm
<b>Diameter</b>	210 mm
<b>Lifespan</b>	35000 Hours
<b>Warranty</b>	3 Years
<b>Mounting type</b>	Recessed
<b>Wiring method</b>	Flex & Plug
<b>LED source</b>	OSRAM
<b>Dimming</b>	Triac Dimming
<b>Constant current/voltage</b>	Constant Current
<b>Material</b>	Thermo Plastic
<b>Lamp Type</b>	LED
<b>Input voltage</b>	220V-240V AC 50HZ
<b>Working temperature</b>	-20°C ~ 45°C



*Photometric information available upon request.*



## LED DOWNLT 3K/4K CCT MUST ADD DRIVER 14W/20W/30W

### Product Specifications

<b>SKU</b>	VBLDL-436-1-CCT
<b>Luminaire efficacy</b>	105 lm/W
<b>Product Series</b>	VBLDL-4X6-SERIES
<b>EAN</b>	9340994019277
<b>Light Colour</b>	3000K, 4000K
<b>Lumen output</b>	2100 lm
<b>IP rating</b>	44
<b>CRI</b>	80
<b>Beam Angle</b>	80 Degrees
<b>Trim colour</b>	White
<b>Cut out</b>	175 mm
<b>Diameter</b>	210 mm
<b>Height</b>	89 mm
<b>Lifespan</b>	35000 Hours
<b>Warranty</b>	5 Years
<b>LED source</b>	OSRAM
<b>Input voltage</b>	220V-240V AC 50HZ
<b>Working temperature</b>	-20°C ~ 45°C



LM-80



*Photometric information available upon request.*