



17.5W 3CCT TRACK LIGHT 3K CRI90+ 50D TRIAC DIM BLK

Product Specifications

SKU	VBLTL-601-4-3K90
Luminaire efficacy	105 lm/W
Track type	3 Circuit
Product Series	VBLTL-601-SERIES
EAN	9340994024028
Wattage	20 W
Lumen output	2100 lm
IP rating	20
CRI	90
Beam Angle	36 Degrees
Trim colour	Black
Lifespan	50000 Hours
Warranty	5 Years
Mounting type	Track
LED source	CITIZEN
Dimming	Triac Dimming
Material	ALUMINUM
Lamp Type	LED
Input voltage	240 Volt AC 50HZ
Working temperature	-20 - 45 degrees



Photometric information available upon request.



17.5W 3CCT TRACK LIGHT 4K CRI90+ 50D TRIAC DIM BLK

Product Specifications

SKU	VBLTL-601-4-4K90
Luminaire efficacy	105 lm/W
Product Series	VBLTL-601-SERIES
EAN	9340994024035
Wattage	20 W
Lumen output	2100 lm
IP rating	20
CRI	90
Beam Angle	36 Degrees
Trim colour	Black
Lifespan	50000 Hours
Warranty	5 Years
Mounting type	Track
LED source	CITIZEN
Dimming	Triac Dimming
Material	ALUMINUM
Lamp Type	LED
Input voltage	240 Volt AC 50HZ
Working temperature	-20 - 45 degrees



Photometric information available upon request.



17.5W 3CCT TRACK LIGHT 3K CRI90+ 50D TRIAC DIM WHT

Product Specifications

SKU	VBLTL-601-1-3K90
Luminaire efficacy	105 lm/W
Track type	3 Circuit
Product Series	VBLTL-601-SERIES
EAN	9340994024004
Wattage	20 W
Lumen output	2100 lm
IP rating	20
CRI	90
Beam Angle	36 Degrees
Trim colour	White
Lifespan	50000 Hours
Warranty	5 Years
Mounting type	Track
LED source	CITIZEN
Dimming	Triac Dimming
Material	ALUMINUM
Lamp Type	LED
Input voltage	240 Volt AC 50HZ
Working temperature	-20 - 45 degrees



Photometric information available upon request.



17.5W 3CCT TRACK LIGHT 4K CRI90+ 50D TRIAC DIM WHT

Product Specifications

SKU	VBLTL-601-1-4K90
Luminaire efficacy	105 lm/W
Track type	3 Circuit
Product Series	VBLTL-601-SERIES
EAN	9340994024011
Wattage	20 W
Lumen output	2100 lm
IP rating	20
CRI	90
Beam Angle	36 Degrees
Trim colour	White
Lifespan	50000 Hours
Warranty	5 Years
Mounting type	Track
LED source	CITIZEN
Dimming	Triac Dimming
Material	ALUMINUM
Lamp Type	LED
Input voltage	240 Volt AC 50HZ
Working temperature	-20 - 45 degrees



Photometric information available upon request.