

AT5005 Twin

Twin Adjustable wall spot with Glass Diffuser - GU10 LED lamp

included

Features

- Discrete installation of sets screws
- Tempered Glass lens
- Elegant Design
- Suitable for coastal environments



Mechanical

Adjustability	Adjustable
Body Material	Aluminium
Diffuser Material	Glass
Product Finish	Powder coated
Fitting Colour	White
IC Rating	Non-IC
Installation Type	Wall or Ceiling
IP Rating	IP65

Electrical

Electrical Rating (Class)	1
Input Frequency (Hz)	50
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
Maximum Wattage (w)	12
Switch Type	Inline
System Max Wattage (W)	12
Working Temp Range (C)	-10 to 40

Lamp

Beam Angle (Deg)	36
Bulb Type	Inbuilt
CCT Configuration	Single
Globe Base	GU10
Globe Included	Yes
Maximum Bulb Wattage (W)	6
Number of Lamps	2
System Efficiency (L/W)	78

Colour temperature

CCT (K)	4000
CCT Colour	Cool White
LED Wattage (W)	6
System Lumens (L)	940

Driver

Dimmable	No
Driver Included	Yes
Integrated Driver	Yes
Driver Type	Fixed output
Wiring Type	Re-wireable terminal block (3 pin)



Compliance

Standards	AS/NZS 60598.1 AS/NZS 60598.2.1
------------------	------------------------------------

Warranty

Commercial Use Warranty	1 (Yr) RTB
Domestic Use Warranty	1 (Yr) RTB

Dimensions

Product Height (mm)	170
Product Length (mm)	100
Product Width (mm)	60

Ordering Information

Order code	16112
Description	AT5005/TWIN/WHT/LED~Twin 2 x 6W LED White Adjustable Wall Spot
Item Code	AT5005/TWIN/WHT/LED

AT5005 Twin 6W

Twin 6W Adjustable wall spot with Glass Diffuser - GU10 LED

lamp included

Features

- Discrete installation of sets screws with matching back plate
- Precision-cut clear glass diffuser
- 90°, Tilt & 270°, Swivel
- Elegant Design
- Suitable for coastal environments
- High quality materials and finishes



Mechanical

Adjustability	Adjustable
Body Material	Aluminium
Diffuser Material	Glass
Product Finish	Anodised
Fitting Colour	Silver
IC Rating	Non-IC
Installation Type	Wall or Ceiling
IP Rating	IP65

Electrical

Electrical Rating (Class)	1
Input Frequency (Hz)	50
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
Maximum Wattage (w)	12
Switch Type	Inline
System Max Wattage (W)	12
Working Temp Range (C)	-10 to 40

Lamp

Beam Angle (Deg)	36
Bulb Type	Inbuilt
CCT Configuration	Single
Globe Base	GU10
Globe Included	Yes
Maximum Bulb Wattage (W)	6
Number of Lamps	2
System Efficiency (L/W)	78

Colour temperature

CCT (K)	4000
CCT Colour	Cool White
LED Wattage (W)	6
System Lumens (L)	940

Driver

Dimmable	No
Driver Included	Yes
Integrated Driver	Yes
Driver Type	Fixed output
Wiring Type	Re-wireable terminal block (3 pin)



Compliance

Standards	AS/NZS 60598.1 AS/NZS 60598.2.1
------------------	------------------------------------

Warranty

Commercial Use Warranty	1 (Yr) RTB
Domestic Use Warranty	1 (Yr) RTB

Dimensions

Product Height (mm)	170
Product Length (mm)	100
Product Width (mm)	60

Ordering Information

Order code	12557
Description	AT5005/TWIN/AND/LED~Twin 2 x 6W LED Anodised Aluminium Adjustable Wall Spot
Item Code	AT5005/TWIN/AND/LED