



3x5-F-P Series

VBLFT-325-F-P



Featuring a high quality aluminium body, choice of clear or frosted cover, unique rotatable end cap and an energy saving of up to 60% the LED Tube Lamps make great direct replacements for T8 fluorescent lamps. Enhances the display of meat products.

- High quality aluminium body with excellent heat dissipation
- •Direct replacement for T8 fluorescent Lamps
- Comes with frosted PC cover & rotatable end caps
- Energy saving potential up to 60%
- Equipped with high power EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 5 year warranty

SKU	VBLFT-325-F-P
Luminaire efficacy	65
EAN	9340994402338
Weight	0.5
Light Colour	Pink
Wattage	8
Lumen output	520
IP rating	20
CRI	80
Beam Angle	120
Base Type	G13
Diameter	29
Length	588
Lifespan	50000
Warranty	5
Dimmable	Non-Dimmable
LED source	Epistar
Material	Aluminium Alloy & PC Frosted Cover
Lamp Type	LED
Input voltage	85V-265V AC 50-60HZ
Diffuser	Opal
Weatherproof	Non-weatherproof
Working temperature	-20°C ~ 40°C
Box Qty	25



Dimensional Drawings









3X5-F-P Series

VBLFT-335-F-P



Featuring a high quality aluminium body, choice of clear or frosted cover, unique rotatable end cap and an energy saving of up to 60% the LED Tube Lamps make great direct replacements for T8 fluorescent lamps. Enhances the display of meat products.

- High quality aluminium body with excellent heat dissipation
- Direct replacement for T8 fluorescent Lamps
- Comes with frosted PC cover & rotatable end caps
- Equipped saving potential up to 60%
- Equipped with high power EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 5 year warranty

SKU	VBLFT-335-F-P
Luminaire efficacy	60
EAN	9340994402345
Weight	0.5
Light Colour	Pink
Wattage	12
Lumen output	720
CRI	80
Beam Angle	120
Base Type	G13
Diameter	29
Length	894
Lifespan	50000
Warranty	5
Dimmable	Non-Dimmable
LED source	Epistar
Material	Aluminium Alloy & PC Frosted Cover
Lamp Type	LED
Input voltage	85V-265V AC 50-60HZ
Diffuser	Opal
Working temperature	-20°C ~ 40°C
Box Qty	25



Dimensional Drawings









3X5-F-P Series

VBLFT-345-F-P



Vibes LED Meat Tube has a unique pink spectrum which makes them ideal for food enhancing purposes, it is environmentally friendly (does not contain harmful substances) and has a high quality aluminium body with excellent heat dissipation.

- High quality aluminium body with excellent heat dissipation
- Direct replacement for T8 fluorescent Lamps
- Comes with frosted PC cover & rotatable end caps
- Equipped saving potential up to 60%
- Equipped with high power EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 5 year warranty

SKU	VBLFT-345-F-P
Luminaire efficacy	68
EAN	9340994016184
Light Colour	Pink
Wattage	16
Lumen output	1088
CRI	80
Beam Angle	120
Base Type	G13
Diameter	29
Length	1198
Lifespan	50000
Warranty	5
Dimmable	Non-Dimmable
LED source	Epistar
Material	Aluminium Alloy & PC Frosted Cover
Lamp Type	LED
Input voltage	85V-265V AC 50-60HZ
Diffuser	Opal
Weatherproof	Non-weatherproof
Working temperature	-20°C ~ 40°C
Box Qty	25



Dimensional Drawings









3X5-F-P Series

VBLFT-355-F-P



Featuring a high quality aluminium body, choice of clear or frosted cover, unique rotatable end cap and an energy saving of up to 60% the LED Tube Lamps make great direct replacements for T8 fluorescent lamps. Enhances the display of meat products.

- High quality aluminium body with excellent heat dissipation
- Direct replacement for T8 fluorescent Lamps
- Comes with frosted PC cover & rotatable end caps
- Equipped saving potential up to 60%
- Equipped with high power EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 5 year warranty

SKU	VBLFT-355-F-P
Luminaire efficacy	66
EAN	9340994402352
Weight	0.5
Light Colour	Pink
Wattage	26
Lumen output	1716
IP rating	20
CRI	80
Beam Angle	120
Base Type	G13
Diameter	29
Length	1498
Lifespan	50000
Warranty	5
Dimmable	Non-Dimmable
LED source	Epistar
Material	Aluminium Alloy & PC Frosted Cover
Lamp Type	LED
Input voltage	85V-265V AC 50-60HZ
Diffuser	Opal
Weatherproof	Non-weatherproof
Working temperature	-20°C ~ 40°C
Box Qty	25



Dimensional Drawings



