



VBLST-096WW-20



Our 9.6W, 24V, 3000K VIBE COB LED Strip delivers superb continuous, seamless light output. Using VIBE COB LED Strip Lighting compared to standard SMD LED Strip Lighting allows you to use no profile (aluminium backing recommended) OR any one of our profile options on a variety of surfaces without unsightly shadowing. Supplied in 5m rolls or ask your reseller for custom cut and assembly options. Available in a Cool White & Warm White and with a colour rendering of CRI 90, colours are accurate for a more vibrant project finish.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

SKU	VBLST-096WW-20
Luminaire efficacy	118
EAN	9340994023236
Light Colour	Warm White
Wattage	9.6
Lumen output	1134
IP rating	20
CRI	90
Beam Angle	120
Cut out	50mm Cutting Intervals, Spaced 7.14mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.



VBLST-096WW-54



Our 9.6W, 24V, 3000K VIBE COB LED Strip delivers superb continuous, seamless light output. Using VIBE COB LED Strip Lighting compared to standard SMD LED Strip Lighting allows you to use no profile (aluminium backing recommended) OR any one of our profile options on a variety of surfaces without unsightly shadowing. Supplied in 5m rolls or ask your reseller for custom cut and assembly options. Available in a Cool White & Warm White and with a colour rendering of CRI 90, colours are accurate for a more vibrant project finish.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

SKU	VBLST-096WW-54
Luminaire efficacy	118
EAN	9340994023731
Light Colour	Warm White
Wattage	9.6
Lumen output	1134
IP rating	54
CRI	90
Beam Angle	120
Cut out	50mm Cutting Intervals, Spaced 7.14mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.



VBLST-096CW-20



Our 9.6W, 24V, 3000K VIBE COB LED Strip delivers superb continuous, seamless light output. Using VIBE COB LED Strip Lighting compared to standard SMD LED Strip Lighting allows you to use no profile (aluminium backing recommended) OR any one of our profile options on a variety of surfaces without unsightly shadowing. Supplied in 5m rolls or ask your reseller for custom cut and assembly options. Available in a Cool White & Warm White and with a colour rendering of CRI 90, colours are accurate for a more vibrant project finish.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

SKU	VBLST-096CW-20
Luminaire efficacy	124
EAN	9340994023243
Light Colour	Cool White
Wattage	9.6
Lumen output	1197
IP rating	20
CRI	90
Beam Angle	120
Cut out	50mm Cutting Intervals, Spaced 7.14mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.



VBLST-096CW-54



Our 9.6W, 24V, 3000K VIBE COB LED Strip delivers superb continuous, seamless light output. Using VIBE COB LED Strip Lighting compared to standard SMD LED Strip Lighting allows you to use no profile (aluminium backing recommended) OR any one of our profile options on a variety of surfaces without unsightly shadowing. Supplied in 5m rolls or ask your reseller for custom cut and assembly options. Available in a Cool White & Warm White and with a colour rendering of CRI 90, colours are accurate for a more vibrant project finish.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

SKU	VBLST-096CW-54
Luminaire efficacy	124
EAN	9340994023724
Light Colour	Cool White
Wattage	9.6
Lumen output	1197
IP rating	54
CRI	90
Beam Angle	120
Cut out	50mm Cutting Intervals, Spaced 7.14mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.



VBLST-096NW-20



Our 9.6W, 24V, 3000K VIBE COB LED Strip delivers superb continuous, seamless light output. Using VIBE COB LED Strip Lighting compared to standard SMD LED Strip Lighting allows you to use no profile (aluminium backing recommended) OR any one of our profile options on a variety of surfaces without unsightly shadowing. Supplied in 5m rolls or ask your reseller for custom cut and assembly options. Available in a Cool White & Warm White and with a colour rendering of CRI 90, colours are accurate for a more vibrant project finish.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

SKU	VBLST-096NW-20
Luminaire efficacy	124
EAN	9340994023250
Light Colour	Natural White
Wattage	9.6
Lumen output	1197
IP rating	20
CRI	90
Beam Angle	120
Cut out	50mm Cutting Intervals, Spaced 7.14mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.



VBLST-096NW-54



Our 9.6W, 24V, 3000K VIBE COB LED Strip delivers superb continuous, seamless light output. Using VIBE COB LED Strip Lighting compared to standard SMD LED Strip Lighting allows you to use no profile (aluminium backing recommended) OR any one of our profile options on a variety of surfaces without unsightly shadowing. Supplied in 5m rolls or ask your reseller for custom cut and assembly options. Available in a Cool White & Warm White and with a colour rendering of CRI 90, colours are accurate for a more vibrant project finish.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

SKU	VBLST-096NW-54
Luminaire efficacy	124
EAN	9340994023717
Light Colour	Natural White
Wattage	9.6
Lumen output	1197
IP rating	20
CRI	90
Beam Angle	120
Cut out	50mm Cutting Intervals, Spaced 7.14mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.