

VBLST-048WW-20



Specifications

SKU	VBLST-048WW-20
Luminaire efficacy	118
EAN	9340994023205
Light Colour	Warm White
Wattage	4.8
Lumen output	567
IP rating	20
CRI	90
Beam Angle	120
Cut out	100mm Cutting Intervals, Spaced 14.29mm
Lifespan	50000
Warranty	3
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.

VBLST-048WW-54



Specifications

SKU	VBLST-048WW-54
Luminaire efficacy	118
EAN	9340994023694
Light Colour	Warm White
Wattage	4.8
Lumen output	567
IP rating	54
CRI	90
Beam Angle	120
Cut out	100mm Cutting Intervals, Spaced 14.29mm
Lifespan	50000
Warranty	3
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.

VBLST-048CW-20



Specifications

SKU	VBLST-048CW-20
Luminaire efficacy	124
EAN	9340994023212
Light Colour	Cool White
Wattage	4.8
Lumen output	598
IP rating	20
CRI	90
Beam Angle	120
Cut out	100mm Cutting Intervals, Spaced 14.29mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C

Photometric information available upon request.

VBLST-048CW-54



Specifications

SKU	VBLST-048CW-54
Luminaire efficacy	124
EAN	9340994023687
Light Colour	Cool White
Wattage	4.8
Lumen output	598
IP rating	54
CRI	90
Beam Angle	120
Cut out	100mm Cutting Intervals, Spaced 14.29mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.

VBLST-048NW-20



Specifications

SKU	VBLST-048NW-20
Luminaire efficacy	124
EAN	9340994023229
Light Colour	Natural White
Wattage	4.8
Lumen output	598
IP rating	20
CRI	90
Beam Angle	120
Cut out	100mm Cutting Intervals, Spaced 14.29mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.

VBLST-048NW-54



Specifications

SKU	VBLST-048NW-54
Luminaire efficacy	124
EAN	9340994023700
Light Colour	Natural White
Wattage	4.8
Lumen output	598
IP rating	54
CRI	90
Beam Angle	120
Cut out	100mm Cutting Intervals, Spaced 14.29mm
Lifespan	50000
Warranty	3
Constant current/voltage	Constant Voltage
LED source	SMD
Accessories	VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type	LED
Dimming	PWM
Input voltage	24 Volt DC
Wiring method	Fly Leads
Working temperature	-20°C ~ 45°C



Photometric information available upon request.