

Last modification

2022-11-03

### MARINA 36-850 9329501041833



#### **Overview**

Family name Marina
Categories Battens
Mounting Surface

Usage Indoor Lighting,Trade Selection

### Color / Material

Fixture ColorGrey,Opal MattFixture MaterialPolycarbonate

Canopy Color Grey

Diffuser MaterialPolycarbonateDiffuser ColorOpal Matt

### Size

Fixture Length (cm)118.0Fixture Width (cm)8.6Fixture Height (cm)6.6Fixture Projection (cm)6.6

### **Specification**

Voltage Input 240V Wattage (max) 36

**Globe Type** LED integrated SMD

Globe / Light Source qty Globe / Light Source included Yes 3250 Lumens Cool White **Color Temperature** 5000k **Color Kelvin Color Rendering** >80 **Dimmable** No **Power Factor** >0.90 **Surge Protection** Yes (1.5 Kva) **Current Output** 480

All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.

NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.



**Electrical Protection** CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP65
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth

Replacement Warranty \*3 Years

<u>Barcode</u>

**GTIN** 9329501041833

**Image -dimensions** 









All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.

NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.



Last modification

2022-11-03

### MARINA 18-850 9329501041826



#### **Overview**

Family name Marina
Categories Battens
Mounting Surface

Usage Indoor Lighting,Trade Selection

### Color / Material

Fixture ColorGrey,Opal MattFixture MaterialPolycarbonate

Canopy Color Grey

Diffuser MaterialPolycarbonateDiffuser ColorOpal Matt

### Size

Fixture Length (cm)59.0Fixture Width (cm)8.6Fixture Height (cm)6.6Fixture Projection (cm)6.6

### **Specification**

Voltage Input 240V Wattage (max) 18

**Globe Type** LED integrated SMD

Globe / Light Source qty Globe / Light Source included Yes Lumens 1600 Cool White **Color Temperature** 5000k **Color Kelvin Color Rendering** >80 **Dimmable** No **Power Factor** >0.90 **Surge Protection** Yes (1.5 Kva) **Current Output** 240

All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.

NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

1



**Electrical Protection** CLASS I - HIGH VOLTAGE, EARTH REQUIRED

IP rating IP65
Lead and Plug No
Approvals RCM
Assembly Required No

Box ContentsBasic mounting screws, InstructionInstallation RequiredYes (by Licensed Electrician only)


Care Instructions Do not use strong liquid cleaners, Wipe clean with a dry cloth

Replacement Warranty \*3 Years

**Barcode** 

**GTIN** 9329501041826

**Image -dimensions** 



All representations within this document are subject to copyright.ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.

NOTE: All images, descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.