



VBLFL-20W-4-CW



Two distinctive features of this 20W Cool White floodlight range include uniquely designed reflector cells which provide low glare and prohibit any light spillage onto neighboring businesses or surrounding residential properties. The other standout feature is a breather valve located on the side of the floods which stops moisture entering the fitting, reducing condensation and prolonging the life of the flood.

Features & Benefits


- Advanced input under/over voltage protection for improved reliability
- Equipped with SMALITE high voltage LED chips
- Available in Black trim only
- Breather valve allows to adjust the floodlights capacity pressure to avoid the formation of water vapour inside the fitting
- Comes complete with 600mm cable
- IP66 rated
- 50,000 hour lifespan
- 2 year warranty

Specifications

SKU	VBLFL-20W-4-CW
Luminaire efficacy	100
EAN	9340994025261
Light Colour	Cool White
Wattage	20
Lumen output	2000
IP rating	66
CRI	70
Beam Angle	110
Trim colour	Black
Length	160
Width	20
Height	147
Lifespan	50000
Warranty	2
Mounting type	Surface
LED source	Smalite
Lamp Type	LED
Input voltage	220V-240V AC 50HZ
Wiring method	Hardwire
Weatherproof	Weatherproof
Working temperature	-30 to 45 degrees
Kelvin	4000K



Dimensional Drawings



Photometric information available upon request.