

The STEAMFORCE® Range

Powerful professional dry steam cleaning



SF Compact

SF Vac Kit

SF Eco

SF 3

SF 6

SF 10

SF 20

	SF Compact M5000	SF Eco M6054	SF Vac Kit * M7005	SF 3 M6055	SF 6 M6067	SF 10 M6055	SF 20 M6052
Power Supply	230v 50Hz	230v 50Hz. 13Amp	230v 50Hz 13 Amp	230v 50Hz 13Amp	400v 50Hz 16Amp	400v 50Hz 16Amp	400v 50Hz 32Amp
Maximum Power	2,200 Watts	3,000 Watts	1,200 Watts	3,000 Watts	5,500 Watts	10,000 Watts	19,500 Watts
Steam Pressure	6.0 Bar nominal	6.0 Bar nominal	N/A	8.0 Bar nominal	10.0 Bar nominal	10.0 Bar nominal	10.0 Bar nominal
Boiler Capacity	2.1 Litres	2.3 Litres	N/A	3.6 Litres	3.6 Litres	6.0 Litres	16 Litres
Water Tank Capacity	2.0 Litres	5.0 Litres	N/A	5.0 Litres	5.0 Litres	10.0 Litres <i>Optional Direct Fill</i>	20.0 Litres <i>Optional Direct Fill</i>
Detergent Capacity	N/A	2 x 5 Litres	N/A	2 x 5 Litres	2 x 5 Litres	2 x 5 Litres	2 x 5 Litres
Vacuum / Vac Tank Capacity	N/A	N/A	1,200 W / 10 L	1,200 W / 10 L <i>Optional</i>	1,200 W / 10 L <i>Optional</i>	1,200 W / 10 L <i>Optional</i>	N/A
Heating Up Time	<i>Approx. 8 minutes</i>	<i>Approx. 5 minutes</i>	N/A	<i>Approx. 9 minutes</i>	<i>Approx. 6 minutes</i>	<i>Approx. 7 minutes</i>	<i>Approx. 7 minutes</i>
Autonomy	<i>Continuous Operation</i>	<i>Continuous Operation</i>	<i>Continuous Operation</i>	<i>Continuous Operation</i>	<i>Continuous Operation</i>	<i>Continuous Operation</i>	<i>Continuous Operation</i>
Machine Dimensions (cm)	40 x 54 x 41.5	37 x 82.5 x 100	60 x 41 x 69	50 x 82.5 x 100	50 x 82.5 x 100	57 x 89 x 104	55 x 100 x 93
Net Weight	10.5 Kg	25 Kg	13.4 Kg	28 Kg	32 Kg	56 Kg	110 Kg
Max. Boiler Temperature	165 °C	165 °C	N/A	175 °C	185 °C	185 °C	185 °C
Recommended Daily Usage	2 - 4 Hours	6 - 8 Hours	8+ Hours	8+ Hours	8+ Hours	8+ Hours	8+ Hours
* Compatible with the SF 3, SF 6 & SF 10							



OSPREYDEEPCLEAN®
DRY STEAM CLEANING TECHNOLOGY

CALL US ON
+44 (0) 1242 513 123

EMAIL US AT
info@ospreydc.com

FOLLOW US
 **@osprey-deepclean**
 **@Ospreydc**
 **@Ospreydc**