

The **i**Steam Range

Industrial, industrious cleaning



iS18




iS36



iS80 Oil

	iS18 M2400167	iS36 M2400198	iS80 Oil M2400157
Power Supply	400v 50Hz 25amp	400v 50Hz 51amp	230v 50Hz 1.5amp
Maximum Power	18 kW	36 kW	80 kW
Steam Pressure	10 Bar nominal	10 Bar nominal	10 Bar nominal
Boiler Capacity	23 Litres	23 Litres	Optional
Detergent Capacity	5 Litres	5 Litres	20 Litres
Steam Production Dry / Wet	23 kg/h - 48 kg/h	46 kg - 96 kg/h	78 kg/h - 168 kg/h
Heating Up Time	Approx. 5 minutes	Approx. 5 minutes	Approx. 5 minutes
Autonomy	Continuous Operation	Continuous Operation	Continuous Operation
Machine Dimensions (cm)	120 x 80 x 110	120 x 80 x 110	125 x 59 x 84
Net Weight	140 Kg	140 Kg	180 Kg
Max. Boiler Temperature	Wet: 150 °C Dry: 160°C	Wet: 150 °C Dry: 160°C	180 °C
Recommended Daily Usage	8+ Hours	8+ Hours	8+ Hours



OSPREY DEEPCLEAN[®]
DRY STEAM CLEANING TECHNOLOGY

CALL US ON
+44 (0) 1242 513 123

EMAIL US AT
info@ospreydc.com

FOLLOW US

 **@osprey-deepclean**

 **@Ospreydc**

 **@Ospreydc**