



Prelude™

Clear Water-Based Wood Primer

For use on rough cut siding, old porous wood, media blasted and pressure washed surfaces, areas where wood has been replaced and other interior and exterior porous vertical wood surfaces.

One coat of Prelude: **For use with LIFELINE™ brand stains.**

- Prevents over absorption of pigmented stain.
- Retards graying due to sunlight (UV) exposure.
- Helps eliminate blotches and streaks.
- Reduces the amount of stain required to cover a surface.

Application Instructions

Inspection

Check for signs of deterioration and decay. Remove and replace or repair deteriorated wood. Unsound wood should be repaired prior to applying Prelude. Contact any Perma-Chink Systems office for information about wood repairs.

Surface Preparation

All surfaces should be free from discolorations and contaminants including media grit, dirt, dust, grayed wood, mold and mildew, old finishes, water repellents and wax. Borate applications such as Shell-Guard®, Shell-Guard® RTU, or Armor-Guard® MUST be accomplished before applying Prelude. Follow labeled product directions.

If more than a week has passed since the exterior has been cleaned or borate treated, wash down the surface of the logs with a solution of Log Wash™, rinse well and allow to dry before applying Prelude. Interior surfaces should be clean and dry.

Application

Stir thoroughly before and regularly during use. Prelude can be applied with a brush or airless sprayer. Do not apply when the surface temperature is below 40° F or above 90° F. DO NOT APPLY TO HOT SURFACES OR IN DIRECT SUNLIGHT. Although Prelude is clear, back brushing is required to work the product into the wood and to assure complete coverage of the surface.

Once the Prelude has dried (typically two to four hours depending on weather conditions) you will be ready to apply any water-based LIFELINE brand stain. Follow the product application directions when applying any stain.

NOTE: PRELUDE IS A PRIMER/SEALER AND IS NOT SUITABLE AS A CLEAR, FINAL FINISH!

Coverage Rate

One gallon of Prelude will cover approximately 200 to 300 square feet on rough or blasted wood surfaces and 350 to 450 square feet on smooth wood surfaces.

Cleanup

Clean area and equipment immediately with warm, soapy water. For sprayers and other commercial equipment, follow the manufacturer's directions. For removing Prelude that has dried, soften with alcohol or mineral spirits and then clean with warm water. Please do not pollute our environment. Dispose of containers and unused material in accordance with local, state, and federal regulations.

Storage

Store Prelude out of direct sunlight and **protect from freezing**. Although Prelude is freeze-thaw stable, if the product is accidentally frozen, allow to thaw, mix well and check for suitability of use before applying.

LIMITED WARRANTY


Perma-Chink Systems, Inc. warrants and represents that PERMA-CHINK PRODUCTS will conform to the description and specifications previously set forth and be free from defects in material and workmanship when shipped to the buyer. EXCEPT WHEN HEREIN EXPRESSLY STATED, THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, APPLICABLE TO THIS PRODUCT. PERMA-CHINK SYSTEMS, INC. EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

CAUTION - DO NOT TAKE INTERNALLY

STIR WELL BEFORE USING



Eastern Division 1-800-548-3554
 Western Division 1-800-548-1231
 Colorado 1-800-433-8781
 Minnesota 1-877-244-6548
 Montana 1-800-479-7090



5 gallons (18.9 liters)

MADE IN USA