



L1000 – C2 Loft Interior Latex Flat

Technical Specifications

PRODUCT DESCRIPTION			
L1000 C2 Loft Interior Latex Flat is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. L1000 is specifically formulated to provide maximum coverage, spatterless application and virtually invisible touch-up.			
SPECIFICATIONS			
Type:	Acrylic/Vinyl Acrylic Blend	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's	Dry Time - Recoat:	2 to 4 Hours
Bases:	White, Pastel, Accent	Full Service:	14 Days
Gloss:	2.5 max @ 85 degrees	Flash Point:	None
		VOC:	Less than 50 g/L
		% Solids Volume:	32.4%
		Weight Per Gallon:	11.31 +/- .2
PRODUCT USE			
<p align="center">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Loft Interior Latex Flat.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Loft Interior Latex Flat.</p> <p>New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Loft Interior Latex Flat.</p>		<p align="center">Application</p> <p>L1000 C2 Loft Interior Latex Flat, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead or mercury			



L1100 – C2 Loft Interior Latex Matte

Technical Specifications

PRODUCT DESCRIPTION			
L1100 Loft Interior Latex Matte is an acrylic fortified low odor, scrubbable finish with a low sheen for uniform application in most residential or commercial environments. L1100 is specifically formulated to provide maximum coverage, spatterless application and virtually invisible touch-up.			
SPECIFICATIONS			
Type:	Acrylic/Vinyl Acrylic Blend	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's	Dry Time - Recoat:	2 -4 Hours
Bases:	White, Pastel, Accent	Full Service:	10 Days
Gloss:	5.0 max @ 85°	Flash Point:	None
		VOC:	Less than 50 g/L
		% Solids Volume:	32.4%
		Weight Per Gallon:	11.31 +/- .2
PRODUCT USE			
<p align="center">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Loft Interior Latex Matte.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Loft Interior Latex Matte.</p> <p>New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Loft Interior Latex Matte.</p>		<p align="center">Application</p> <p>L1100 Loft Interior Latex Matte, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead or mercury			



L1200 – C2 Loft Interior Latex Eggshell Technical Specifications

PRODUCT DESCRIPTION			
L1200 C2 Loft Interior Latex Eggshell is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. L1200 is specifically formulated to provide maximum coverage, spatterless application and virtually invisible touch-up.			
SPECIFICATIONS			
Type:	Acrylic/Vinyl Acrylic Blend	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's	Dry Time - Recoat:	2 to 4 Hours
Bases:	White, Pastel, Accent	Full Service:	14 Days
Gloss:	15-25% @ 85 degrees	Flash Point:	None
		VOC:	Less than 50 g/L
		% Solids Volume:	37.7%
		Weight Per Gallon:	11.32 +/- .2
PRODUCT USE			
<p align="center">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Loft Interior Latex Eggshell.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Loft Interior Latex Eggshell.</p> <p>New Wood: Sand entire surface and apply one coat of primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Loft Interior Latex Eggshell.</p>		<p align="center">Application</p> <p>L1200 C2 Loft Interior Latex Eggshell may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead or mercury			



L1300 – C2 Loft Interior Latex Satin Technical Specifications

PRODUCT DESCRIPTION			
L1300 C2 Loft Interior Latex Satin is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. Primarily designed as a trim finish, L1300 is specifically formulated to provide maximum coverage, spatterless application and great touch-up.			
SPECIFICATIONS			
Type:	Acrylic/Vinyl Acrylic Blend	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's	Dry Time - Recoat:	2 to 4 Hours
Bases:	White, Pastel, Accent	Full Service:	14 Days
Gloss:	15-25% @ 60 degrees	Flash Point:	None
		VOC:	Less than 50 g/L
		% Solids Volume:	36.9%
		Weight Per Gallon:	11.91 +/- .2
PRODUCT USE			
Surface preparation		Application	
<p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Loft Interior Latex Satin.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Loft Interior Latex Satin.</p> <p>New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Loft Interior Latex Satin.</p>		<p>L1300 C2 Loft Interior Latex Satin, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead or mercury			



L1400 – C2 Loft Semi-Gloss

Technical Specifications

PRODUCT DESCRIPTION			
L1400 C2 Loft Interior Semi-gloss is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. Primarily designed as a trim finish, L1400 is specifically formulated to provide maximum coverage, spatterless application and great touch-up.			
SPECIFICATIONS			
Type:	Acrylic/Vinyl Acrylic Blend	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's	Dry Time - Recoat:	2 to 4 Hours
Bases:	White, Pastel, Accent	Full Service:	14 Days
Gloss:	45-55% @ 60 degrees	Flash Point:	None
		VOC:	Less than 50 g/L
		% Solids Volume:	36.4%
		Weight Per Gallon:	11.91 +/- .2
PRODUCT USE			
<p align="center">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Loft Interior Latex Semi-Gloss.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Loft Interior Latex Semi-Gloss.</p> <p>New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Loft Interior Latex Semi-Gloss.</p>		<p align="center">Application</p> <p>L1400 C2 Loft Interior Latex Semi-Gloss may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead or mercury			