



C1000 – Interior/Exterior Acrylic Primer/Sealer

PRODUCT DESCRIPTION

C2One is a 100% acrylic stain blocking primer/sealer designed for multiple interior/exterior uses. C2One's terrific adhesion makes application direct to metal surfaces such as galvanized, aluminum and properly prepared steel easy. C2One blocks most stains from water, grease, oil, crayon and ink. C2One may be top-coated with all types of architectural finishes.

SPECIFICATIONS

Type:	Acrylic Resin	Dry Time - Touch:	30 Minutes
Sizes:	1's and Quarts	Dry Time - Recoat:	1 to 2 Hours
Bases:	None – White only	Full Service:	7 Days
Gloss:	4%-6% @ 60°	Flash Point:	None
		VOC:	Less than 50 gm/L
		% Solids Volume:	37.8
		Weight Per Gallon:	11.2 +/- .2

PRODUCT USE

Surface preparation

See your C2 dealer for specific preparation recommendations.

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth then remove sanding dust, spot prime with C2One and then apply one coat of C2One primer to the entire surface.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Apply one coat C2One Primer to entire surface. Finish with one or two coats of desired C2 top coat.

New Wood: Sand wood to remove any grain raising and remove dust before applying one coat of C2One Primer. When primer is dry, sand smooth and remove dust before applying finish coat.

Previously painted surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Pressure wash or power wash exterior surfaces to remove chalk and surface contaminants. If mildew is present, treat with a solution of household bleach and water (1 part bleach to 4 parts water). Use protective clothing, eyewear and rubber gloves when using bleach. Spot prime as required and then apply one coat of C2One primer to the entire surface.

Glossy surfaces: C2One has excellent adhesion to clean glossy surfaces. Ceramic tile, alkyd and factory finishes simply need to be free of surface contaminants for excellent adhesion.

Vinyl, aluminum and masonite siding: Pressure or power wash to remove chalk and other surface contaminants and apply one coat of C2One primer to the entire surface.

Stains and Bleeding woods: For stains, remove as much of the stain as practical prior to primer application with a strong cleaning agent and hot water. Some stains may require two coats of primer to completely block. Bleeding woods such as redwood or cedar generally require one coat of C2One to block the stain. In some cases, severely staining wood may require multiple coats of primer. In the most severe instances an alkyd primer may be required.

Application

C2One Interior/Exterior Acrylic Primer/Sealer may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

Thinning: Do not thin. **Airless Spray:** Use a 12 to 15 mil size tip. (2100 to 2400 psi) **Cleanup:** Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. **Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.**

Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.