



L7300 – C2 Luxe Satin

Technical Specifications

PRODUCT DESCRIPTION			
C2 Luxe Satin is a premium 100% Acrylic coating designed to provide exceptional hiding, adhesion, and washability on interior surfaces. Unsurpassed application properties give all C2 Luxe products a refined hand, a smooth beautiful finish at once elegant and durable.			
SPECIFICATIONS			
Type:	100% Acrylic	Dry Time - Touch:	1 Hour
Sizes:	1's and Quarts	Dry Time - Recoat:	2 to 4 Hours
Bases:	White, Pastel, Midtone, Accent	Full Service:	10 Days
Gloss:	15 - 25% @ 60 ⁰	Flash Point:	None
		VOC:	Less than 50 gm/L
		% Solids Volume:	37
		Weight Per Gallon:	10.83+/- .25
PRODUCT USE			
<p>Surface Preparation: To ensure maximum adhesion remove any and all contaminants (dirt, dust, oil, grease, wax, etc.) from the surface with a thorough washing; and scuff sand all glossy areas, followed by wiping with a clean damp cloth. Consult your local C2 dealer for expert advice on the appropriate primer for specific substrates and surface prep.</p> <p>Application: Stir paint thoroughly prior to application. Make certain air, product and surface temperature is above 50 F (10 C) prior to applying. First quality rollers, brushes, pads, or spray tools must be used to ensure a premium paint job. Your C2 dealer will be happy to recommend the correct tools.</p> <p>Coverage: Covers up to 450 square feet per gallon (40 square meters per 3.78 liters) depending on surface condition and method of application. Be careful not to overspread the paint as hiding problems could occur.</p> <p>Dry Time: Dry to touch - 1 hour. Dry to re-coat - 2 to 4 hours. Dry to use - Allow 10 days before washing surface with non-abrasive cleaning solution.</p>		<p>Cleanup: Clean brushes, rollers, pads, etc. with warm, soapy water immediately after completion of painting.</p> <p>Disposal: See your local C2 dealer for disposal recommendations in your area.</p> <p>First Aid Treatment: In case of eye contact, rinse with clean water for fifteen minutes. Get medical attention if irritation persists. In case of skin contact, wash with water.</p> <p>Keep from freezing.</p> <p>Product application and surface conditions are beyond the control of the manufacturer. Liability, if any, is limited to replacement product only.</p> <p>Check dry sample for correct color match. Neither the manufacturer nor the dealer assumes responsibility for a mismatched color after it has been applied.</p>	