



C2000 – Studio Interior Latex Flat

Technical Specifications

PRODUCT DESCRIPTION			
C2000 C2 Studio Interior Latex Flat is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. C2000 is specifically formulated to provide maximum coverage, spatterless application and virtually invisible touch-up.			
SPECIFICATIONS			
Type:	Acrylic/Vinyl Acrylic Blend	Dry Time - Touch:	30 Minutes
Sizes:	Quarts, 1's, 5's	Dry Time - Recoat:	2 to 4 Hours
Bases:	White, Pastel, Midtone, Accent	Full Service:	14 Days
Gloss:	2.5 max @ 60 degrees	Flash Point:	None
	2.5 max @ 85 degrees	VOC:	Less than 50 g/L
		% Solids Volume:	32.4%
		Weight Per Gallon:	11.31 +/- .2
PRODUCT USE			
<p align="center">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Studio Interior Latex Flat.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Studio Interior Latex Flat.</p> <p>New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Studio Interior Latex Flat.</p>		<p align="center">Application</p> <p>C2000 C2 Studio Interior Latex Flat, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.</p>	
C2 Paint is formulated without lead or mercury			